

Example Programs for KINSOL v2.3.0

Aaron M. Collier and Radu Serban
Center for Applied Scientific Computing
Lawrence Livermore National Laboratory

April 2005

DISCLAIMER

This document was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor the University of California nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or the University of California, and shall not be used for advertising or product endorsement purposes.

This research was supported under the auspices of the U.S. Department of Energy by the University of California, Lawrence Livermore National Laboratory under contract No. W-7405-Eng-48.

Contents

1	Introduction	1
2	C example problems	3
2.1	A serial example: kinwebs	3
2.2	A parallel example: kinwebbbd	5
3	Fortran example problems	7
3.1	A serial example: kindiagsf	7
3.2	A parallel example: kindiagpf	8
	References	10
A	Listing of kinwebs.c	11
B	Listing of kinwebbbd.c	26
C	Listing of kindiagsf.f	45
D	Listing of kindiagpf.f	49

1 Introduction

This report is intended to serve as a companion document to the User Documentation of KINSOL [1]. It provides details, with listings, on the example programs supplied with the KINSOL distribution package.

The KINSOL distribution contains examples of four types: serial C examples, parallel C examples, and serial and parallel FORTRAN examples. The following lists summarize all of these examples.

Supplied in the `sundials/kinsol/examples_ser` directory is the following serial example (using the `NVECTOR_SERIAL` module):

- `kinwebs` is an example program for KINSOL with the Krylov linear solver.

This program solves a nonlinear system that arises from a system of partial differential equations. The PDE system is a six-species food web population model, with predator-prey interaction and diffusion on the unit square in two dimensions. The preconditioner is a block-diagonal matrix based on the partial derivatives of the interaction terms only.

Supplied in the `sundials/kinsol/examples_par` directory are the following two parallel examples (using the `NVECTOR_PARALLEL` module):

- `kinwebp` is a parallel implementation of `kinwebs`.
- `kinwebbbd` solves the same problem as `kinwebp`, with a block-diagonal matrix with banded blocks as a preconditioner, generated by difference quotients, using the module `KINBBDPRE`.

With the `FKINSOL` module, in the directories `sundials/kinsol/fcmix/examples_ser` and `sundials/kinsol/fcmix/examples_par`, are the following examples for the FORTRAN-C interface:

- `kindiagsf` is a serial example, which solves a nonlinear system of the form $u_i^2 = i^2$ using an approximate diagonal preconditioner.
- `kindiagpf` is a parallel implementation of `kindiagsf`.

In the following sections, we give detailed descriptions of some (but not all) of these examples. The Appendices contain complete listings of those examples described below. We also give our output files for each of these examples, but users should be cautioned that their results may differ slightly from these. Differences in solution values may differ within the tolerances, and differences in cumulative counters, such as numbers of Newton iterations, may differ from one machine environment to another by as much as 10% to 20%.

In the descriptions below, we make frequent references to the KINSOL User Document [1]. All citations to specific sections (e.g. §5.1) are references to parts of that User Document, unless explicitly stated otherwise.

Note. The examples in the KINSOL distribution are written in such a way as to compile and run for any combination of configuration options during the installation of SUNDIALS (see §2). As a consequence, they contain portions of code that will not be typically

present in a user program. For example, all C example programs make use of the variable `SUNDIALS_EXTENDED_PRECISION` to test if the solver libraries were built in extended precision and use the appropriate conversion specifiers in `printf` functions. Similarly, the FORTRAN examples in FKINSOL are automatically pre-processed to generate source code that corresponds to the precision in which the KINSOL libraries were built (see §3 in this document for more details).

2 C example problems

2.1 A serial example: kinwebs

We give here an example that illustrates the use of KINSOL with the Krylov method SPGMR, in the KINSPGMR module, as the linear system solver. The source file, `kinwebs.c`, is listed in Appendix A.

This program solves a nonlinear system that arises from a discretized system of partial differential equations. The PDE system is a six-species food web population model, with predator-prey interaction and diffusion on the unit square in two dimensions. Given the dependent variable vector of species concentrations $c = [c_1, c_2, \dots, c_{n_s}]^T$, where $n_s = 2n_p$ is the number of species and n_p is the number of predators and of prey, then the PDEs can be written as

$$d_i \cdot \left(\frac{\partial^2 c_i}{\partial x^2} + \frac{\partial^2 c_i}{\partial y^2} \right) + f_i(x, y, c) = 0 \quad (i = 1, \dots, n_s), \quad (1)$$

where the subscripts i are used to distinguish the species, and where

$$f_i(x, y, c) = c_i \cdot \left(b_i + \sum_{j=1}^{n_s} a_{i,j} \cdot c_j \right). \quad (2)$$

The problem coefficients are given by

$$a_{ij} = \begin{cases} -1 & i = j \\ -0.5 \cdot 10^{-6} & i \leq n_p, j > n_p \\ 10^4 & i > n_p, j \leq n_p \\ 0 & \text{all other,} \end{cases}$$

$$b_i = b_i(x, y) = \begin{cases} 1 + \alpha xy & i \leq n_p \\ -1 - \alpha xy & i > n_p, \end{cases}$$

and

$$d_i = \begin{cases} 1 & i \leq n_p \\ 0.5 & i > n_p. \end{cases}$$

The spatial domain is the unit square $(x, y) \in [0, 1] \times [0, 1]$.

Homogeneous Neumann boundary conditions are imposed and the initial guess is constant in both x and y . For this example, the equations (1) are discretized spatially with standard central finite differences on a 8×8 mesh with $n_s = 6$, giving a system of size 384.

Among the initial `#include` lines in this case are lines to include `kinspgmr.h` and `sundialsmath.h`. The first contains constants and function prototypes associated with the SPGMR method. The inclusion of `sundialsmath.h` is done to access the `MAX` and `ABS` macros, and the `RSqrt` function to compute the square root of a `realtype` number.

The `main` program calls `KINCreate` and then calls `KINMalloc` with the name of the user-supplied system function `func` and solution vector as arguments. The `main` program then calls a number of `KINSet*` routines to notify KINSOL of the function data pointer, the positivity constraints on the solution, and convergence tolerances on the system function and step size. It calls `KINSpgmr` (see §5.4.2) to specify the KINSPGMR linear solver, and passes a value of 15 as the maximum Krylov subspace dimension, `max1`. Next, a maximum

value of `maxlrst = 2` restarts is imposed and the user-supplied preconditioner setup and solve functions, `PrecSetupBD` and `PrecSolveBD`, and the pointer to user data are specified through a call to `KINSpgrmrSetPreconditioner` (see §5.4.4). The `data` pointer passed to `KINSpgrmrSetPreconditioner` is passed to `PrecSetupBD` and `PrecSolveBD` whenever these are called.

Next, `KINSol` is called, the return value is tested for error conditions, and the approximate solution vector is printed via a call to `PrintOutput`. After that, `PrintFinalStats` is called to get and print final statistics, and memory is freed by calls to `N_VDestroy_Serial`, `FreeUserData` and `KINFree`. The statistics printed are the total numbers of nonlinear iterations (`nni`), of `func` evaluations (excluding those for Jv product evaluations) (`nfe`), of `func` evaluations for Jv evaluations (`nfeSG`), of linear (Krylov) iterations (`nli`), of preconditioner evaluations (`npe`), and of preconditioner solves (`nps`). All of these optional outputs and others are described in §5.4.5.

Mathematically, the dependent variable has three dimensions: species number, x mesh point, and y mesh point. But in `NVECTOR_SERIAL`, a vector of type `N_Vector` works with a one-dimensional contiguous array of data components. The macro `IJ_Vptr` isolates the translation from three dimensions to one. Its use results in clearer code and makes it easy to change the underlying layout of the three-dimensional data. Here the problem size is 384, so we use the `NV_DATA_S` macro for efficient `N_Vector` access. The `NV_DATA_S` macro gives a pointer to the first component of a serial `N_Vector` which is then passed to the `IJ_Vptr` macro.

The preconditioner used here is the block-diagonal part of the true Newton matrix and is based only on the partial derivatives of the interaction terms f in (2) and hence its diagonal blocks are $n_s \times n_s$ matrices ($n_s = 6$). It is generated and factored in the `PrecSetupBD` routine and backsolved in the `PrecSolveBD` routine. See §5.5.4 for detailed descriptions of these preconditioner functions.

The program `kinwebs.c` uses the “small” dense functions for all operations on the 6×6 preconditioner blocks. Thus it includes `smalldense.h`, and calls the small dense matrix functions `denalloc`, `denallocpiv`, `denfree`, `denfreepiv`, `gefa`, and `gesl`. The small dense functions are generally available for KINSOL user programs (for more information, see §8.1 or the comments in the header file `smalldense.h`).

In addition to the functions called by KINSOL, `kinwebs.c` includes definitions of several private functions. These are: `AllocUserData` to allocate space for P and the pivot arrays; `InitUserData` to load problem constants in the `data` block; `FreeUserData` to free that block; `SetInitialProfiles` to load the initial values in `cc`; `PrintOutput` to retrieve and print selected solution values; `PrintFinalStats` to print statistics; and `check_flag` to check return values for error conditions.

The output generated by `kinwebs` is shown below. Note that the solution involved 7 Newton iterations, with an average of about 33 Krylov iterations per Newton iteration.

kinwebs sample output

```

Predator-prey test problem -- KINSol (serial version)

Mesh dimensions = 8 X 8
Number of species = 6
Total system size = 384

Flag globalstrategy = 1 (1 = Inex. Newton, 2 = Linesearch)

```

```

Linear solver is SPGMR with maxl = 15, maxlrst = 2
Preconditioning uses interaction-only block-diagonal matrix
Positivity constraints imposed on all components
Tolerance parameters: fnormtol = 1e-07   scsteptol = 1e-13

```

```

Initial profile of concentration
At all mesh points:  1 1 1   30000 30000 30000

```

```

Computed equilibrium species concentrations:

```

```

At bottom left:
  1.16428 1.16428 1.16428 34927.5 34927.5 34927.5

```

```

At top right:
  1.25797 1.25797 1.25797 37736.7 37736.7 37736.7

```

```

Final Statistics..

```

```

nni   =    7    nli   =   230
nfe   =    8    nfeSG =   237
nps   =   237    npe   =    1    ncfl  =    4

```

2.2 A parallel example: kinwebbbd

In this example, `kinwebbbd`, we solve the same problem as with `kinwebs` above, but in parallel, and instead of supplying the preconditioner we use the `KINBBDPRE` module. The source is given in Appendix B.

`KINBBDPRE` generates and uses a band-block-diagonal preconditioner, generated by difference quotients. The upper and lower half-bandwidths of the Jacobian block on each process are both equal to $2 \cdot \text{NUM_SPECIES} - 1$, and that is the value supplied as `mu` and `m1` in the call to `KINBBDPrecAlloc`.

In this case, we think of the parallel MPI processes as being laid out in a rectangle, and each process being assigned a subgrid of size $\text{MXSUB} \times \text{MYSUB}$ of the $x - y$ grid. If there are `NPEX` processes in the x direction and `NPEY` processes in the y direction, then the overall grid size is $\text{MX} \times \text{MY}$ with $\text{MX} = \text{NPEX} \times \text{MXSUB}$ and $\text{MY} = \text{NPEY} \times \text{MYSUB}$, and the size of the nonlinear system is $\text{NUM_SPECIES} \cdot \text{MX} \cdot \text{MY}$.

The evaluation of the nonlinear system function is performed in `func`. In this parallel setting, the processes first communicate the subgrid boundary data and then compute the local components of the nonlinear system function. The MPI communication is isolated in the private function `ccomm` (which in turn calls `BRecvPost`, `BSend`, and `BRecvWait`) and the subgrid boundary data received from neighboring processes is loaded into the work array `cext`. The computation of the nonlinear system function is done in `func_local` which starts by copying the local segment of the `cc` vector into `cext` and then by imposing the boundary conditions by copying the first interior mesh line from `cc` into `cext`. After this, the nonlinear system function is evaluated by using central finite-difference approximations using the data in `cext` exclusively.

The function `func_local` is also passed as the `gloc` argument to `KINBBDPrecAlloc`.

Since all communication needed for the evaluation of the local approximation of f used in building the band-block-diagonal preconditioner is already done for the evaluation of f in `func`, a NULL pointer is passed as the `gcomm` argument to `KINBBDPrecAlloc`.

The `main` program resembles closely that of the `kinwebs` example, with particularization arising from the use of the parallel MPI `NVECTOR_PARALLEL` module. It begins by initializing MPI and obtaining the total number of processes and the id of the local process. The local length of the solution vector is then computed as `NUM_SPECIES*MXSUB*MYSUB`. Distributed vectors are created by calling the constructor defined in `NVECTOR_PARALLEL` with the MPI communicator and the local and global problem sizes as arguments. All output is performed only from the process with id equal to 0. Finally, after all memory deallocation, the MPI environment is terminated by calling `MPI_Finalize`.

The output generated by `kinwebbbd` is shown below.

```

----- kinwebbbd sample output -----

Predator-prey test problem-- KINSol (parallel-BBD version)

Mesh dimensions = 20 X 20
Number of species = 6
Total system size = 2400

Subgrid dimensions = 10 X 10
Processor array is 2 X 2

Flag globalstrategy = 1 (1 = Inex. Newton, 2 = Linesearch)
Linear solver is SPGMR with maxl = 20, maxlrst = 2
Preconditioning uses band-block-diagonal matrix from KINBBDPRE
  with matrix half-bandwidths ml, mu = 11 11
Tolerance parameters: fnormtol = 1e-07  scsteptol = 1e-13

Initial profile of concentration
At all mesh points: 1 1 1 30000 30000 30000

Computed equilibrium species concentrations:

At bottom left:
1.165 1.165 1.165 34949 34949 34949

At top right:
1.25552 1.25552 1.25552 37663.2 37663.2 37663.2

Final Statistics..

nni   =    10    nli   =   540
nfe   =    11    nfeSG =   550
nps   =   550    npe   =    1    ncfl  =    7

```

3 Fortran example problems

The FORTRAN example problem programs supplied with the KINSOL package are all written in standard F77 Fortran and use double-precision arithmetic. However, when the FORTRAN examples are built, the source code is automatically modified according to the configure options supplied by the user and the system type. Integer variables are declared as `INTEGER*n`, where n denotes the number of bytes in the corresponding C type (`long int` or `int`). Floating-point variable declarations remain unchanged if double-precision is used, but are changed to `REAL*n`, where n denotes the number of bytes in the SUNDIALS type `realtype`, if using single-precision. Also, if using single-precision, declarations of floating-point constants are appropriately modified, e.g.; `0.5D-4` is changed to `0.5E-4`.

The two examples supplied with the FKINSOL module are very simple tests of the FORTRAN-C interface module. They solve the nonlinear system

$$F(u) = 0, \quad \text{where } f_i(u) = u_i^2 - i^2, 1 \leq i \leq N.$$

3.1 A serial example: kindiagsf

The `kindiagsf` program, for which the source code is listed in Appendix C, solves the above problem using the serial `NVECTOR_SERIAL` module.

The main program begins by calling `fnvinit`s to initialize computations with the serial `NVECTOR_SERIAL` module. Next, the array `uu` is set to contain the initial guess $u_i = 2i$, the array `scale` is set with all components equal to 1.0 (meaning that no scaling is done), and the array `constr` is set with all components equal to 0.0 to indicate that no inequality constraints should be imposed on the solution vector.

The KINSOL solver is initialized and memory for it is allocated by calling `fkinmalloc`, which also specifies the maximum number of iterations between calls to the preconditioner setup routine (`msbpre = 5`), the tolerance for stopping based on the function norm (`fnormtol = 10-5`), the tolerance for stopping based on the step length (`scsteptol = 10-4`), and that no optional inputs are provided (`inopt = 0`).

Next, the KINSPGMR linear solver module is attached to KINSOL by calling `fkinspgmr`, which also specifies the maximum Krylov subspace dimension (`maxl = 10`) and the maximum number of restarts allowed for SPGMR (`maxlrst = 2`). The KINSPGMR module is directed to use the supplied preconditioner by calling the `fkinspgmrsetprec` routine with a first argument equal to 1. The solution of the nonlinear system is obtained after a successful return from `fkinsol`, which is then printed to unit 6 (stdout).

Memory allocated for the KINSOL solver is released by calling `fkinfree` and computations with the `NVECTOR_SERIAL` module are terminated by calling `fnvfree`s.

The user-supplied routine `fkfun` contains a straightforward transcription of the nonlinear system function f , while the routine `fkpset` sets the array `pp` (in the common block `pcom`) to contain an approximation to the reciprocals of the Jacobian diagonal elements. The components of `pp` are then used in `fkpsol` to solve the preconditioner linear system $Px = v$ through simple multiplications.

The following is sample output from `kindiagsf`, using $N = 128$.

— kindiagsf sample output —

Example program kindiagsf:

This fkinsol example code solves a 128 eqn diagonal algebraic system.

Its purpose is to demonstrate the use of the Fortran interface in a serial environment.

```
globalstrategy = KIN_INEXACT_NEWTON
```

```
FKINSOL return code is 0
```

The resultant values of uu are:

1	1.000000	2.000000	3.000000	4.000000
5	5.000000	6.000000	7.000000	8.000000
9	9.000000	10.000000	11.000000	12.000000
13	13.000000	14.000000	15.000000	16.000000
17	17.000000	18.000000	19.000000	20.000000
21	21.000000	22.000000	23.000000	24.000000
25	25.000000	26.000000	27.000000	28.000000
29	29.000000	30.000000	31.000000	32.000000
33	33.000000	34.000000	35.000000	36.000000
37	37.000000	38.000000	39.000000	40.000000
41	41.000000	42.000000	43.000000	44.000000
45	45.000000	46.000000	47.000000	48.000000
49	49.000000	50.000000	51.000000	52.000000
53	53.000000	54.000000	55.000000	56.000000
57	57.000000	58.000000	59.000000	60.000000
61	61.000000	62.000000	63.000000	64.000000
65	65.000000	66.000000	67.000000	68.000000
69	69.000000	70.000000	71.000000	72.000000
73	73.000000	74.000000	75.000000	76.000000
77	77.000000	78.000000	79.000000	80.000000
81	81.000000	82.000000	83.000000	84.000000
85	85.000000	86.000000	87.000000	88.000000
89	89.000000	90.000000	91.000000	92.000000
93	93.000000	94.000000	95.000000	96.000000
97	97.000000	98.000000	99.000000	100.000000
101	101.000000	102.000000	103.000000	104.000000
105	105.000000	106.000000	107.000000	108.000000
109	109.000000	110.000000	111.000000	112.000000
113	113.000000	114.000000	115.000000	116.000000
117	117.000000	118.000000	119.000000	120.000000
121	121.000000	122.000000	123.000000	124.000000
125	125.000000	126.000000	127.000000	128.000000

Final statistics:

```
nni = 7, nli = 21, nfe = 8, npe = 2, nps = 28, ncfl = 0
```

3.2 A parallel example: kindiagpf

The program `kindiagpf`, listed in Appendix D, is a straightforward modification of `kindiagsf` to use the parallel MPI `NVECTOR_PARALLEL` module.

After initialization of MPI, the NVECTOR_PARALLEL module is initialized by calling `fnvinitp` with the local and global vector sizes as its first two arguments. The problem set-up (KINSOL initialization, KINSPGMR specification) and solution steps are the same as in `kindiagsf`. Upon successful return from `fkinsol`, the solution segment local to the process with id equal to 0 is printed to the screen. Finally, the KINSOL memory is released, NVECTOR_PARALLEL computations are finalized, and the MPI environment is terminated.

For this simple example, no inter-process communication is required to evaluate the nonlinear system function f or the preconditioner. As a consequence, the user-supplied routines `fkfun`, `fkpset`, and `fkpsol` are basically identical to those in `kindiagsf`.

Sample output from `kindiapg`, for $N = 128$, follows.

```

_____ kindiapg sample output _____
Example program kindiapg:

This fkinsol example code solves a 128 eqn diagonal algebraic system.
Its purpose is to demonstrate the use of the Fortran interface
in a parallel environment.

globalstrategy = KIN_INEXACT_NEWTON

FKINSOL return code is      0

The resultant values of uu (process 0) are:

  1  1.000000  2.000000  3.000000  4.000000
  5  5.000000  6.000000  7.000000  8.000000
  9  9.000000 10.000000 11.000000 12.000000
 13 13.000000 14.000000 15.000000 16.000000
 17 17.000000 18.000000 19.000000 20.000000
 21 21.000000 22.000000 23.000000 24.000000
 25 25.000000 26.000000 27.000000 28.000000
 29 29.000000 30.000000 31.000000 32.000000

Final statistics:

nni =    7,  nli =   21,  nfe =    8,  npe =    2,  nps=  28,  ncfl=   0

```

References

- [1] A. M. Collier, A. C. Hindmarsh, R. Serban, and C.S. Woodward. User Documentation for KINSOL v2.2.0. Technical Report UCRL-SM-208116, LLNL, 2004.

A Listing of kinwebs.c

```

1  /*
2  * -----
3  * $Revision: 1.14.2.3 $
4  * $Date: 2005/04/07 00:15:48 $
5  * -----
6  * Programmer(s): Allan Taylor, Alan Hindmarsh and
7  *                Radu Serban @ LLNL
8  * -----
9  * Example (serial):
10 *
11 * This example solves a nonlinear system that arises from a system
12 * of partial differential equations. The PDE system is a food web
13 * population model, with predator-prey interaction and diffusion
14 * on the unit square in two dimensions. The dependent variable
15 * vector is the following:
16 *
17 *      1      2      ns
18 * c = ( c , c , ..., c ) (denoted by the variable cc)
19 *
20 * and the PDE's are as follows:
21 *
22 *      i      i
23 *      0 = d(i)*(c  + c  ) + f (x,y,c) (i=1,...,ns)
24 *             xx      yy      i
25 *
26 * where
27 *
28 *      i      ns      j
29 *      f (x,y,c) = c * (b(i) + sum a(i,j)*c )
30 *      i      j=1
31 *
32 * The number of species is ns = 2 * np, with the first np being
33 * prey and the last np being predators. The number np is both the
34 * number of prey and predator species. The coefficients a(i,j),
35 * b(i), d(i) are:
36 *
37 * a(i,i) = -AA (all i)
38 * a(i,j) = -GG (i <= np , j > np)
39 * a(i,j) = EE (i > np, j <= np)
40 * b(i) = BB * (1 + alpha * x * y) (i <= np)
41 * b(i) = -BB * (1 + alpha * x * y) (i > np)
42 * d(i) = DPREY (i <= np)
43 * d(i) = DPRED ( i > np)
44 *
45 * The various scalar parameters are set using define's or in
46 * routine InitUserData.
47 *
48 * The boundary conditions are: normal derivative = 0, and the
49 * initial guess is constant in x and y, but the final solution
50 * is not.
51 *
52 * The PDEs are discretized by central differencing on an MX by

```

```

53  * MY mesh.
54  *
55  * The nonlinear system is solved by KINSOL using the method
56  * specified in local variable globalstrat.
57  *
58  * The preconditioner matrix is a block-diagonal matrix based on
59  * the partial derivatives of the interaction terms f only.
60  *
61  * Constraints are imposed to make all components of the solution
62  * positive.
63  * -----
64  * References:
65  *
66  * 1. Peter N. Brown and Youcef Saad,
67  *   Hybrid Krylov Methods for Nonlinear Systems of Equations
68  *   LLNL report UCRL-97645, November 1987.
69  *
70  * 2. Peter N. Brown and Alan C. Hindmarsh,
71  *   Reduced Storage Matrix Methods in Stiff ODE systems,
72  *   Lawrence Livermore National Laboratory Report UCRL-95088,
73  *   Rev. 1, June 1987, and Journal of Applied Mathematics and
74  *   Computation, Vol. 31 (May 1989), pp. 40-91. (Presents a
75  *   description of the time-dependent version of this test
76  *   problem.)
77  * -----
78  */
79
80 #include <stdio.h>
81 #include <stdlib.h>
82 #include <math.h>
83 #include "kinsol.h"          /* main KINSOL header file          */
84 #include "kinspgmr.h"        /* use KINSPGMR linear solver      */
85 #include "sundialstypes.h"    /* def's of realtype and booleantype */
86 #include "nvector_serial.h"   /* definitions of type N_Vector and access macros */
87 #include "iterative.h"        /* contains the enum for types of preconditioning */
88 #include "smalldense.h"       /* use generic DENSE solver for preconditioning */
89 #include "sundialsmath.h"     /* contains RSqrt routine          */
90
91 /* Problem Constants */
92
93 #define NUM_SPECIES      6 /* must equal 2*(number of prey or predators)
94                            number of prey = number of predators */
95
96 #define PI               RCONST(3.1415926535898) /* pi */
97
98 #define MX               8 /* MX = number of x mesh points */
99 #define MY               8 /* MY = number of y mesh points */
100 #define NSMX             (NUM_SPECIES * MX)
101 #define NEQ              (NSMX * MY) /* number of equations in the system */
102 #define AA               RCONST(1.0) /* value of coefficient AA in above eqns */
103 #define EE               RCONST(10000.) /* value of coefficient EE in above eqns */
104 #define GG               RCONST(0.5e-6) /* value of coefficient GG in above eqns */
105 #define BB               RCONST(1.0) /* value of coefficient BB in above eqns */
106 #define DPREY            RCONST(1.0) /* value of coefficient dprey above */

```

```

107 #define DPRED      RCONST(0.5)    /* value of coefficient dpred above */
108 #define ALPHA      RCONST(1.0)    /* value of coefficient alpha above */
109 #define AX         RCONST(1.0)    /* total range of x variable */
110 #define AY         RCONST(1.0)    /* total range of y variable */
111 #define FTOL       RCONST(1.e-7)  /* ftol tolerance */
112 #define STOL       RCONST(1.e-13) /* stol tolerance */
113 #define THOUSAND   RCONST(1000.0) /* one thousand */
114 #define ZERO       RCONST(0.)     /* 0. */
115 #define ONE        RCONST(1.0)    /* 1. */
116 #define TWO        RCONST(2.0)    /* 2. */
117 #define PREYIN     RCONST(1.0)    /* initial guess for prey concentrations. */
118 #define PREDIN     RCONST(30000.0)/* initial guess for predator concs.    */
119
120 /* User-defined vector access macro: IJ_Vptr */
121
122 /* IJ_Vptr is defined in order to translate from the underlying 3D structure
123    of the dependent variable vector to the 1D storage scheme for an N-vector.
124    IJ_Vptr(vv,i,j) returns a pointer to the location in vv corresponding to
125    indices is = 0, jx = i, jy = j.    */
126
127 #define IJ_Vptr(vv,i,j)    (&NV_Ith_S(vv, i*NUM_SPECIES + j*NSMX))
128
129 /* Type : UserData
130    contains preconditioner blocks, pivot arrays, and problem constants */
131
132 typedef struct {
133     realtype **P[MX] [MY];
134     long int *pivot[MX] [MY];
135     realtype **acoef, *bcoef;
136     N_Vector rates;
137     realtype *cox, *coy;
138     realtype ax, ay, dx, dy;
139     realtype ound, sqround;
140     long int mx, my, ns, np;
141 } *UserData;
142
143 /* Functions Called by the KINSOL Solver */
144
145 static void func(N_Vector cc, N_Vector fval, void *f_data);
146
147 static int PrecSetupBD(N_Vector cc, N_Vector cscale,
148                       N_Vector fval, N_Vector fscale,
149                       void *P_data,
150                       N_Vector vtemp1, N_Vector vtemp2);
151
152 static int PrecSolveBD(N_Vector cc, N_Vector cscale,
153                       N_Vector fval, N_Vector fscale,
154                       N_Vector vv, void *P_data,
155                       N_Vector ftem);
156
157 /* Private Helper Functions */
158
159 static UserData AllocUserData(void);
160 static void InitUserData(UserData data);

```

```

161 static void FreeUserData(UserData data);
162 static void SetInitialProfiles(N_Vector cc, N_Vector sc);
163 static void PrintHeader(int globalstrategy, int maxl, int maxlrst,
164                         realtype fnormtol, realtype scsteptol);
165 static void PrintOutput(N_Vector cc);
166 static void PrintFinalStats(void *kmem);
167 static void WebRate(realtype xx, realtype yy, realtype *cxy, realtype *ratesxy,
168                   void *f_data);
169 static realtype DotProd(long int size, realtype *x1, realtype *x2);
170 static int check_flag(void *flagvalue, char *funcname, int opt);
171
172 /*
173  *-----
174  * MAIN PROGRAM
175  *-----
176  */
177
178 int main(void)
179 {
180     int globalstrategy;
181     realtype fnormtol, scsteptol;
182     N_Vector cc, sc, constraints;
183     UserData data;
184     int flag, maxl, maxlrst;
185     void *kmem;
186
187     cc = sc = constraints = NULL;
188     kmem = NULL;
189     data = NULL;
190
191     /* Allocate memory, and set problem data, initial values, tolerances */
192     globalstrategy = KIN_INEXACT_NEWTON;
193
194     data = AllocUserData();
195     if (check_flag((void *)data, "AllocUserData", 2)) return(1);
196     InitUserData(data);
197
198     /* Create serial vectors of length NEQ */
199     cc = N_VNew_Serial(NEQ);
200     if (check_flag((void *)cc, "N_VNew_Serial", 0)) return(1);
201     sc = N_VNew_Serial(NEQ);
202     if (check_flag((void *)sc, "N_VNew_Serial", 0)) return(1);
203     data->rates = N_VNew_Serial(NEQ);
204     if (check_flag((void *)data->rates, "N_VNew_Serial", 0)) return(1);
205
206     constraints = N_VNew_Serial(NEQ);
207     if (check_flag((void *)constraints, "N_VNew_Serial", 0)) return(1);
208     N_VConst(TWO, constraints);
209
210     SetInitialProfiles(cc, sc);
211
212     fnormtol=FTOL; scsteptol=STOL;
213
214     /* Call KINCreate/KINMalloc to initialize KINSOL:

```

```

215     nvSpec is the nvSpec pointer used in the serial version
216     A pointer to KINSOL problem memory is returned and stored in kmem. */
217     kmem = KINCreate();
218     if (check_flag((void *)kmem, "KINCreate", 0)) return(1);
219     /* Vector cc passed as template vector. */
220     flag = KINMalloc(kmem, func, cc);
221     if (check_flag(&flag, "KINMalloc", 1)) return(1);
222
223     flag = KINSetFdata(kmem, data);
224     if (check_flag(&flag, "KINSetFdata", 1)) return(1);
225     flag = KINSetConstraints(kmem, constraints);
226     if (check_flag(&flag, "KINSetConstraints", 1)) return(1);
227     flag = KINSetFuncNormTol(kmem, fnormtol);
228     if (check_flag(&flag, "KINSetFuncNormTol", 1)) return(1);
229     flag = KINSetScaledStepTol(kmem, scsteptol);
230     if (check_flag(&flag, "KINSetScaledStepTol", 1)) return(1);
231
232     /* We no longer need the constraints vector since KINSetConstraints
233        creates a private copy for KINSOL to use. */
234     N_VDestroy_Serial(constraints);
235
236     /* Call KINSpgrmr to specify the linear solver KINSPGMR with preconditioner
237        routines PrecSetupBD and PrecSolveBD, and the pointer to the user block data. */
238     maxl = 15;
239     maxlrst = 2;
240     flag = KINSpgrmr(kmem, maxl);
241     if (check_flag(&flag, "KINSpgrmr", 1)) return(1);
242
243     flag = KINSpgrmrSetMaxRestarts(kmem, maxlrst);
244     if (check_flag(&flag, "KINSpgrmrSetMaxRestarts", 1)) return(1);
245     flag = KINSpgrmrSetPreconditioner(kmem,
246                                     PrecSetupBD,
247                                     PrecSolveBD,
248                                     data);
249     if (check_flag(&flag, "KINSpgrmrSetPreconditioner", 1)) return(1);
250
251     /* Print out the problem size, solution parameters, initial guess. */
252     PrintHeader(globalstrategy, maxl, maxlrst, fnormtol, scsteptol);
253
254     /* Call KINSol and print output concentration profile */
255     flag = KINSol(kmem, /* KINSol memory block */
256                 cc, /* initial guess on input; solution vector */
257                 globalstrategy, /* global strategy choice */
258                 sc, /* scaling vector, for the variable cc */
259                 sc); /* scaling vector for function values fval */
260     if (check_flag(&flag, "KINSol", 1)) return(1);
261
262     printf("\n\nComputed equilibrium species concentrations:\n");
263     PrintOutput(cc);
264
265     /* Print final statistics and free memory */
266     PrintFinalStats(kmem);
267
268     N_VDestroy_Serial(cc);

```

```

269     N_VDestroy_Serial(sc);
270     KINFree(kmem);
271     FreeUserData(data);
272
273     return(0);
274 }
275
276 /* Readability definitions used in other routines below */
277
278 #define acoef  (data->acoef)
279 #define bcoef  (data->bcoef)
280 #define cox    (data->cox)
281 #define coy    (data->coy)
282
283 /*
284  *-----
285  * FUNCTIONS CALLED BY KINSOL
286  *-----
287  */
288
289 /*
290  * System function for predator-prey system
291  */
292
293 static void func(N_Vector cc, N_Vector fval, void *f_data)
294 {
295     realtype xx, yy, delx, dely, *cxy, *rxy, *fxy, dcyli, dcyui, dcxli, dcxri;
296     long int jx, jy, is, idyu, idyl, idxr, idxl;
297     UserData data;
298
299     data = (UserData)f_data;
300     delx = data->dx;
301     dely = data->dy;
302
303     /* Loop over all mesh points, evaluating rate array at each point*/
304     for (jy = 0; jy < MY; jy++) {
305
306         yy = dely*jy;
307
308         /* Set lower/upper index shifts, special at boundaries. */
309         idyl = (jy != 0) ? NSMX : -NSMX;
310         idyu = (jy != MY-1) ? NSMX : -NSMX;
311
312         for (jx = 0; jx < MX; jx++) {
313
314             xx = delx*jx;
315
316             /* Set left/right index shifts, special at boundaries. */
317             idxl = (jx != 0) ? NUM_SPECIES : -NUM_SPECIES;
318             idxr = (jx != MX-1) ? NUM_SPECIES : -NUM_SPECIES;
319
320             cxy = IJ_Vptr(cc, jx, jy);
321             rxy = IJ_Vptr(data->rates, jx, jy);
322             fxy = IJ_Vptr(fval, jx, jy);

```

```

323
324     /* Get species interaction rate array at (xx,yy) */
325     WebRate(xx, yy, cxy, rxy, f_data);
326
327     for(is = 0; is < NUM_SPECIES; is++) {
328
329         /* Differencing in x direction */
330         dcyli = *(cxy+is) - *(cxy - idyl + is) ;
331         dcyui = *(cxy + idyu + is) - *(cxy+is);
332
333         /* Differencing in y direction */
334         dcxli = *(cxy+is) - *(cxy - idxl + is);
335         dcxri = *(cxy + idxr + is) - *(cxy+is);
336
337         /* Compute the total rate value at (xx,yy) */
338         fxy[is] = (coy)[is] * (dcyui - dcyli) +
339                 (cox)[is] * (dcxri - dcxli) + rxy[is];
340
341     } /* end of is loop */
342
343 } /* end of jx loop */
344
345 } /* end of jy loop */
346 }
347
348 /*
349  * Preconditioner setup routine. Generate and preprocess P.
350  */
351
352 static int PrecSetupBD(N_Vector cc, N_Vector cscale,
353                       N_Vector fval, N_Vector fscale,
354                       void *P_data,
355                       N_Vector vtemp1, N_Vector vtemp2)
356 {
357     realtype r, r0, uround, sqruround, xx, yy, delx, dely, csave, fac;
358     realtype *cxy, *scxy, **Pxy, *ratesxy, *Pxycol, perturb_rates[NUM_SPECIES];
359     long int i, j, jx, jy, ret;
360     UserData data;
361
362     data = (UserData) P_data;
363     delx = data->dx;
364     dely = data->dy;
365
366     uround = data->uround;
367     sqruround = data->sqruround;
368     fac = N_VWL2Norm(fval, fscale);
369     r0 = THOUSAND * uround * fac * NEQ;
370     if(r0 == ZERO) r0 = ONE;
371
372     /* Loop over spatial points; get size NUM_SPECIES Jacobian block at each */
373     for (jy = 0; jy < MY; jy++) {
374         yy = jy*dely;
375
376         for (jx = 0; jx < MX; jx++) {

```

```

377     xx = jx*delx;
378     Pxy = (data->P)[jx][jy];
379     cxy = IJ_Vptr(cc,jx,jy);
380     scxy= IJ_Vptr(cscale,jx,jy);
381     ratesxy = IJ_Vptr((data->rates),jx,jy);
382
383     /* Compute difference quotients of interaction rate fn. */
384     for (j = 0; j < NUM_SPECIES; j++) {
385
386         csave = cxy[j]; /* Save the j,jx,jy element of cc */
387         r = MAX(sqruround*ABS(csave), r0/scxy[j]);
388         cxy[j] += r; /* Perturb the j,jx,jy element of cc */
389         fac = ONE/r;
390
391         WebRate(xx, yy, cxy, perturb_rates, data);
392
393         /* Restore j,jx,jy element of cc */
394         cxy[j] = csave;
395
396         /* Load the j-th column of difference quotients */
397         Pxycol = Pxy[j];
398         for (i = 0; i < NUM_SPECIES; i++)
399             Pxycol[i] = (perturb_rates[i] - ratesxy[i]) * fac;
400
401     } /* end of j loop */
402
403     /* Do LU decomposition of size NUM_SPECIES preconditioner block */
404     ret = gefa(Pxy, NUM_SPECIES, (data->pivot)[jx][jy]);
405     if (ret != 0) return(1);
406
407 } /* end of jx loop */
408
409 } /* end of jy loop */
410
411 return(0);
412 }
413
414 /*
415  * Preconditioner solve routine
416  */
417
418 static int PrecSolveBD(N_Vector cc, N_Vector cscale,
419                       N_Vector fval, N_Vector fscale,
420                       N_Vector vv, void *P_data,
421                       N_Vector ftem)
422 {
423     realtype **Pxy, *vxy;
424     long int *piv, jx, jy;
425     UserData data;
426
427     data = (UserData)P_data;
428
429     for (jx=0; jx<MX; jx++) {

```

```

431
432     for (jy=0; jy<MY; jy++) {
433
434         /* For each (jx,jy), solve a linear system of size NUM_SPECIES.
435            vxy is the address of the corresponding portion of the vector vv;
436            Pxy is the address of the corresponding block of the matrix P;
437            piv is the address of the corresponding block of the array pivot. */
438         vxy = IJ_Vptr(vv,jx,jy);
439         Pxy = (data->P)[jx][jy];
440         piv = (data->pivot)[jx][jy];
441         gesl (Pxy, NUM_SPECIES, piv, vxy);
442
443     } /* end of jy loop */
444
445 } /* end of jx loop */
446
447 return(0);
448 }
449
450 /*
451  * Interaction rate function routine
452  */
453
454 static void WebRate(realtype xx, realtype yy, realtype *cxy, realtype *ratesxy,
455                    void *f_data)
456 {
457     long int i;
458     realtype fac;
459     UserData data;
460
461     data = (UserData)f_data;
462
463     for (i = 0; i<NUM_SPECIES; i++)
464         ratesxy[i] = DotProd(NUM_SPECIES, cxy, acoef[i]);
465
466     fac = ONE + ALPHA * xx * yy;
467
468     for (i = 0; i < NUM_SPECIES; i++)
469         ratesxy[i] = cxy[i] * ( bcoef[i] * fac + ratesxy[i] );
470 }
471
472 /*
473  * Dot product routine for realtype arrays
474  */
475
476 static realtype DotProd(long int size, realtype *x1, realtype *x2)
477 {
478     long int i;
479     realtype *xx1, *xx2, temp = ZERO;
480
481     xx1 = x1; xx2 = x2;
482     for (i = 0; i < size; i++) temp += (*xx1++) * (*xx2++);
483
484     return(temp);

```

```

485 }
486
487 /*
488 *-----
489 * PRIVATE FUNCTIONS
490 *-----
491 */
492
493 /*
494 * Allocate memory for data structure of type UserData
495 */
496
497 static UserData AllocUserData(void)
498 {
499     int jx, jy;
500     UserData data;
501
502     data = (UserData) malloc(sizeof *data);
503
504     for (jx=0; jx < MX; jx++) {
505         for (jy=0; jy < MY; jy++) {
506             (data->P)[jx][jy] = denalloc(NUM_SPECIES);
507             (data->pivot)[jx][jy] = denallocpiv(NUM_SPECIES);
508         }
509     }
510     acoef = denalloc(NUM_SPECIES);
511     bcoef = (realtype *)malloc(NUM_SPECIES * sizeof(realtype));
512     cox   = (realtype *)malloc(NUM_SPECIES * sizeof(realtype));
513     coy   = (realtype *)malloc(NUM_SPECIES * sizeof(realtype));
514
515     return(data);
516 }
517
518 /*
519 * Load problem constants in data
520 */
521
522 static void InitUserData(UserData data)
523 {
524     long int i, j, np;
525     realtype *a1,*a2, *a3, *a4, dx2, dy2;
526
527     data->mx = MX;
528     data->my = MY;
529     data->ns = NUM_SPECIES;
530     data->np = NUM_SPECIES/2;
531     data->ax = AX;
532     data->ay = AY;
533     data->dx = (data->ax)/(MX-1);
534     data->dy = (data->ay)/(MY-1);
535     data->uround = UNIT_ROUNDOFF;
536     data->sqrround = RSqrt(data->uround);
537
538     /* Set up the coefficients a and b plus others found in the equations */

```

```

539     np = data->np;
540
541     dx2=(data->dx)*(data->dx); dy2=(data->dy)*(data->dy);
542
543     for (i = 0; i < np; i++) {
544         a1= &(acoef[i][np]);
545         a2= &(acoef[i+np][0]);
546         a3= &(acoef[i][0]);
547         a4= &(acoef[i+np][np]);
548
549         /* Fill in the portion of acoef in the four quadrants, row by row */
550         for (j = 0; j < np; j++) {
551             *a1++ = -GG;
552             *a2++ = EE;
553             *a3++ = ZERO;
554             *a4++ = ZERO;
555         }
556
557         /* and then change the diagonal elements of acoef to -AA */
558         acoef[i][i]=-AA;
559         acoef[i+np][i+np] = -AA;
560
561         bcoef[i] = BB;
562         bcoef[i+np] = -BB;
563
564         cox[i]=DPREY/dx2;
565         cox[i+np]=DPRED/dx2;
566
567         coy[i]=DPREY/dy2;
568         coy[i+np]=DPRED/dy2;
569     }
570 }
571
572 /*
573  * Free data memory
574  */
575
576 static void FreeUserData(UserData data)
577 {
578     int jx, jy;
579
580     for (jx=0; jx < MX; jx++) {
581         for (jy=0; jy < MY; jy++) {
582             denfree((data->P)[jx][jy]);
583             denfreepiv((data->pivot)[jx][jy]);
584         }
585     }
586
587     denfree(acoef);
588     free(bcoef);
589     free(cox);
590     free(coy);
591     N_VDestroy_Serial(data->rates);
592     free(data);

```

```

593 }
594
595 /*
596  * Set initial conditions in cc
597 */
598
599 static void SetInitialProfiles(N_Vector cc, N_Vector sc)
600 {
601     int i, jx, jy;
602     realtype *cloc, *sloc;
603     realtype ctemp[NUM_SPECIES], stemp[NUM_SPECIES];
604
605     /* Initialize arrays ctemp and stemp used in the loading process */
606     for (i = 0; i < NUM_SPECIES/2; i++) {
607         ctemp[i] = PREYIN;
608         stemp[i] = ONE;
609     }
610     for (i = NUM_SPECIES/2; i < NUM_SPECIES; i++) {
611         ctemp[i] = PREDIN;
612         stemp[i] = RCONST(0.00001);
613     }
614
615     /* Load initial profiles into cc and sc vector from ctemp and stemp. */
616     for (jy = 0; jy < MY; jy++) {
617         for (jx = 0; jx < MX; jx++) {
618             cloc = IJ_Vptr(cc, jx, jy);
619             sloc = IJ_Vptr(sc, jx, jy);
620             for (i = 0; i < NUM_SPECIES; i++) {
621                 cloc[i] = ctemp[i];
622                 sloc[i] = stemp[i];
623             }
624         }
625     }
626 }
627
628 /*
629  * Print first lines of output (problem description)
630 */
631
632 static void PrintHeader(int globalstrategy, int maxl, int maxlrst,
633                        realtype fnormtol, realtype scsteptol)
634 {
635     printf("\nPredator-prey test problem -- KINSol (serial version)\n\n");
636     printf("Mesh dimensions = %d X %d\n", MX, MY);
637     printf("Number of species = %d\n", NUM_SPECIES);
638     printf("Total system size = %d\n\n", NEQ);
639     printf("Flag globalstrategy = %d (1 = Inex. Newton, 2 = Linesearch)\n",
640            globalstrategy);
641     printf("Linear solver is SPGMR with maxl = %d, maxlrst = %d\n",
642            maxl, maxlrst);
643     printf("Preconditioning uses interaction-only block-diagonal matrix\n");
644     printf("Positivity constraints imposed on all components \n");
645     #if defined(SUNDIALS_EXTENDED_PRECISION)
646     printf("Tolerance parameters:  fnormtol = %Lg    scsteptol = %Lg\n",

```

```

647         fnormtol, scsteptol);
648 #elif defined(SUNDIALS_DOUBLE_PRECISION)
649     printf("Tolerance parameters:  fnormtol = %lg    scsteptol = %lg\n",
650           fnormtol, scsteptol);
651 #else
652     printf("Tolerance parameters:  fnormtol = %g    scsteptol = %g\n",
653           fnormtol, scsteptol);
654 #endif
655
656     printf("\nInitial profile of concentration\n");
657 #if defined(SUNDIALS_EXTENDED_PRECISION)
658     printf("At all mesh points:  %Lg %Lg %Lg    %Lg %Lg %Lg\n",
659           PREYIN, PREYIN, PREYIN,
660           PREDIN, PREDIN, PREDIN);
661 #elif defined(SUNDIALS_DOUBLE_PRECISION)
662     printf("At all mesh points:  %lg %lg %lg    %lg %lg %lg\n",
663           PREYIN, PREYIN, PREYIN,
664           PREDIN, PREDIN, PREDIN);
665 #else
666     printf("At all mesh points:  %g %g %g    %g %g %g\n",
667           PREYIN, PREYIN, PREYIN,
668           PREDIN, PREDIN, PREDIN);
669 #endif
670 }
671
672 /*
673  * Print sampled values of current cc
674  */
675
676 static void PrintOutput(N_Vector cc)
677 {
678     int is, jx, jy;
679     realtype *ct;
680
681     jy = 0; jx = 0;
682     ct = IJ_Vptr(cc, jx, jy);
683     printf("\nAt bottom left:");
684
685     /* Print out lines with up to 6 values per line */
686     for (is = 0; is < NUM_SPECIES; is++){
687         if ((is%6)*6 == is) printf("\n");
688         #if defined(SUNDIALS_EXTENDED_PRECISION)
689             printf(" %Lg", ct[is]);
690         #elif defined(SUNDIALS_DOUBLE_PRECISION)
691             printf(" %lg", ct[is]);
692         #else
693             printf(" %g", ct[is]);
694         #endif
695     }
696
697     jy = MY-1; jx = MX-1;
698     ct = IJ_Vptr(cc, jx, jy);
699     printf("\n\nAt top right:");
700

```

```

701  /* Print out lines with up to 6 values per line */
702  for (is = 0; is < NUM_SPECIES; is++) {
703      if ((is%6)*6 == is) printf("\n");
704  #if defined(SUNDIALS_EXTENDED_PRECISION)
705      printf(" %Lg",ct[is]);
706  #elif defined(SUNDIALS_DOUBLE_PRECISION)
707      printf(" %lg",ct[is]);
708  #else
709      printf(" %g",ct[is]);
710  #endif
711  }
712  printf("\n\n");
713  }
714
715  /*
716   * Print final statistics contained in iopt
717   */
718
719  static void PrintFinalStats(void *kmem)
720  {
721      long int nni, nfe, nli, npe, nps, ncfl, nfeSG;
722      int flag;
723
724      flag = KINGGetNumNonlinSolvIters(kmem, &nni);
725      check_flag(&flag, "KINGGetNumNonlinSolvIters", 1);
726      flag = KINGGetNumFuncEvals(kmem, &nfe);
727      check_flag(&flag, "KINGGetNumFuncEvals", 1);
728      flag = KINSpgmrGetNumLinIters(kmem, &nli);
729      check_flag(&flag, "KINSpgmrGetNumLinIters", 1);
730      flag = KINSpgmrGetNumPrecEvals(kmem, &npe);
731      check_flag(&flag, "KINSpgmrGetNumPrecEvals", 1);
732      flag = KINSpgmrGetNumPrecSolves(kmem, &nps);
733      check_flag(&flag, "KINSpgmrGetNumPrecSolves", 1);
734      flag = KINSpgmrGetNumConvFails(kmem, &ncfl);
735      check_flag(&flag, "KINSpgmrGetNumConvFails", 1);
736      flag = KINSpgmrGetNumFuncEvals(kmem, &nfeSG);
737      check_flag(&flag, "KINSpgmrGetNumFuncEvals", 1);
738
739      printf("\nFinal Statistics.. \n\n");
740      printf("nni      = %5ld      nli      = %5ld\n", nni, nli);
741      printf("nfe      = %5ld      nfeSG = %5ld\n", nfe, nfeSG);
742      printf("nps      = %5ld      npe      = %5ld      ncfl = %5ld\n", nps, npe, ncfl);
743
744  }
745
746  /*
747   * Check function return value...
748   *   opt == 0 means SUNDIALS function allocates memory so check if
749   *   returned NULL pointer
750   *   opt == 1 means SUNDIALS function returns a flag so check if
751   *   flag >= 0
752   *   opt == 2 means function allocates memory so check if returned
753   *   NULL pointer
754   */

```

```

755
756 static int check_flag(void *flagvalue, char *funcname, int opt)
757 {
758     int *errflag;
759
760     /* Check if SUNDIALS function returned NULL pointer - no memory allocated */
761     if (opt == 0 && flagvalue == NULL) {
762         fprintf(stderr,
763             "\nSUNDIALS_ERROR: %s() failed - returned NULL pointer\n\n",
764             funcname);
765         return(1);
766     }
767
768     /* Check if flag < 0 */
769     else if (opt == 1) {
770         errflag = (int *) flagvalue;
771         if (*errflag < 0) {
772             fprintf(stderr,
773                 "\nSUNDIALS_ERROR: %s() failed with flag = %d\n\n",
774                 funcname, *errflag);
775             return(1);
776         }
777     }
778
779     /* Check if function returned NULL pointer - no memory allocated */
780     else if (opt == 2 && flagvalue == NULL) {
781         fprintf(stderr,
782             "\nMEMORY_ERROR: %s() failed - returned NULL pointer\n\n",
783             funcname);
784         return(1);
785     }
786
787     return(0);
788 }

```

B Listing of kinwebbbd.c

```

1  /*
2  * -----
3  * $Revision: 1.18.2.2 $
4  * $Date: 2005/04/07 00:15:40 $
5  * -----
6  * Programmer(s): Allan Taylor, Alan Hindmarsh and
7  *                Radu Serban @ LLNL
8  * -----
9  * Example problem for KINSol (parallel machine case) using the BBD
10 * preconditioner.
11 *
12 * This example solves a nonlinear system that arises from a system
13 * of partial differential equations. The PDE system is a food web
14 * population model, with predator-prey interaction and diffusion on
15 * the unit square in two dimensions. The dependent variable vector
16 * is the following:
17 *
18 *      1      2      ns
19 * c = ( c , c , ..., c ) (denoted by the variable cc)
20 *
21 * and the PDE's are as follows:
22 *
23 *      i      i
24 *      0 = d(i)*(c  + c  ) + f (x,y,c) (i=1,...,ns)
25 *      xx      yy      i
26 *
27 * where
28 *
29 *      i      ns      j
30 *      f (x,y,c) = c * (b(i) + sum a(i,j)*c )
31 *      i      j=1
32 *
33 * The number of species is ns = 2 * np, with the first np being
34 * prey and the last np being predators. The number np is both the
35 * number of prey and predator species. The coefficients a(i,j),
36 * b(i), d(i) are:
37 *
38 * a(i,i) = -AA (all i)
39 * a(i,j) = -GG (i <= np , j > np)
40 * a(i,j) = EE (i > np, j <= np)
41 * b(i) = BB * (1 + alpha * x * y) (i <= np)
42 * b(i) = -BB * (1 + alpha * x * y) (i > np)
43 * d(i) = DPREY (i <= np)
44 * d(i) = DPRED ( i > np)
45 *
46 * The various scalar parameters are set using define's or in
47 * routine InitUserData.
48 *
49 * The boundary conditions are: normal derivative = 0, and the
50 * initial guess is constant in x and y, although the final
51 * solution is not.
52 *

```

```

53 * The PDEs are discretized by central differencing on a MX by
54 * MY mesh.
55 *
56 * The nonlinear system is solved by KINSOL using the method
57 * specified in the local variable globalstrat.
58 *
59 * The preconditioner matrix is a band-block-diagonal matrix
60 * using the KINBBDPRE module. The half-bandwidths are:
61 *
62 *   ml = mu = 2*ns - 1
63 * -----
64 * References:
65 *
66 * 1. Peter N. Brown and Youcef Saad,
67 *   Hybrid Krylov Methods for Nonlinear Systems of Equations
68 *   LLNL report UCRL-97645, November 1987.
69 *
70 * 2. Peter N. Brown and Alan C. Hindmarsh,
71 *   Reduced Storage Matrix Methods in Stiff ODE systems,
72 *   Lawrence Livermore National Laboratory Report UCRL-95088,
73 *   Rev. 1, June 1987, and Journal of Applied Mathematics and
74 *   Computation, Vol. 31 (May 1989), pp. 40-91. (Presents a
75 *   description of the time-dependent version of this
76 *   test problem.)
77 * -----
78 * Run command line: mpirun -np N -machinefile machines kinwebbbd
79 * where N = NPEX * NPEY is the number of processors.
80 * -----
81 */
82
83 #include <stdio.h>
84 #include <stdlib.h>
85 #include <math.h>
86 #include "sundialstypes.h" /* def's of realtype and booleantype */
87 #include "kinsol.h" /* main KINSol header file */
88 #include "iterative.h" /* enum for types of preconditioning */
89 #include "kinspgmr.h" /* use KINSpgmr linear solver */
90 #include "smalldense.h" /* use generic DENSE solver for preconditioning*/
91 #include "nvector_parallel.h" /* def's of type N_Vector, macro NV_DATA_P */
92 #include "sundialsmath.h" /* contains RSqrt routine */
93 #include "mpi.h" /* MPI include file */
94 #include "kinbbdpre.h" /* band preconditioner function prototypes */
95
96 /* Problem Constants */
97
98 #define NUM_SPECIES      6 /* must equal 2*(number of prey or predators)
99                            number of prey = number of predators */
100
101 #define PI              RCONST(3.1415926535898) /* pi */
102
103 #define NPEX            2 /* number of processors in the x-direction */
104 #define NPEY            2 /* number of processors in the y-direction */
105 #define MXSUB           10 /* number of x mesh points per subgrid */
106 #define MYSUB           10 /* number of y mesh points per subgrid */

```

```

107 #define MX          (NPEX*MXSUB) /* number of grid points in x-direction */
108 #define MY          (NPEY*MYSUB) /* number of grid points in y-direction */
109 #define NSMXSUB     (NUM_SPECIES * MXSUB)
110 #define NSMXSUB2    (NUM_SPECIES * (MXSUB+2))
111 #define NEQ         (NUM_SPECIES*MX*MY) /* number of equations in system */
112 #define AA          RCONST(1.0) /* value of coefficient AA in above eqns */
113 #define EE          RCONST(10000.) /* value of coefficient EE in above eqns */
114 #define GG          RCONST(0.5e-6) /* value of coefficient GG in above eqns */
115 #define BB          RCONST(1.0) /* value of coefficient BB in above eqns */
116 #define DPRED       RCONST(1.0) /* value of coefficient dpred above */
117 #define DPRED       RCONST(0.5) /* value of coefficient dpred above */
118 #define ALPHA       RCONST(1.0) /* value of coefficient alpha above */
119 #define AX          RCONST(1.0) /* total range of x variable */
120 #define AY          RCONST(1.0) /* total range of y variable */
121 #define FTOL        RCONST(1.e-7) /* ftol tolerance */
122 #define STOL        RCONST(1.e-13) /* stol tolerance */
123 #define THOUSAND    RCONST(1000.0) /* one thousand */
124 #define ZERO        RCONST(0.0) /* 0. */
125 #define ONE         RCONST(1.0) /* 1. */
126 #define PREYIN      RCONST(1.0) /* initial guess for prey concentrations. */
127 #define PREDIN      RCONST(30000.0) /* initial guess for predator concs. */
128
129 /* User-defined vector access macro: IJ_Vptr */
130
131 /* IJ_Vptr is defined in order to translate from the underlying 3D structure
132    of the dependent variable vector to the 1D storage scheme for an N-vector.
133    IJ_Vptr(vv,i,j) returns a pointer to the location in vv corresponding to
134    indices is = 0, jx = i, jy = j. */
135
136 #define IJ_Vptr(vv,i,j) (&NV_Ith_P(vv, i*NUM_SPECIES + j*NSMXSUB))
137
138 /* Type : UserData
139    contains preconditioner blocks, pivot arrays, and problem constants */
140
141 typedef struct {
142     realtype **acoef, *bcoef;
143     N_Vector rates;
144     realtype *cox, *coy;
145     realtype ax, ay, dx, dy;
146     long int Nlocal, mx, my, ns, np;
147     realtype cext[NUM_SPECIES * (MXSUB+2)*(MYSUB+2)];
148     long int my_pe, isubx, suby, nsmxsub, nsmxsub2;
149     MPI_Comm comm;
150 } *UserData;
151
152 /* Function called by the KINSol Solver */
153
154 static void func(N_Vector cc, N_Vector fval, void *f_data);
155
156 static void ccomm(long int Nlocal, N_Vector cc, void *data);
157
158 static void func_local(long int Nlocal, N_Vector cc, N_Vector fval, void *f_data);
159
160 /* Private Helper Functions */

```

```

161
162 static UserData AllocUserData(void);
163 static void InitUserData(long int my_pe, long int Nlocal, MPI_Comm comm, UserData data);
164 static void FreeUserData(UserData data);
165 static void SetInitialProfiles(N_Vector cc, N_Vector sc);
166 static void PrintHeader(int globalstrategy, int maxl, int maxlrst,
167                         long int mu, long int ml,
168                         realtype fnormtol, realtype scsteptol);
169 static void PrintOutput(long int my_pe, MPI_Comm comm, N_Vector cc);
170 static void PrintFinalStats(void *kmem);
171 static void WebRate(realtype xx, realtype yy, realtype *cxy, realtype *ratesxy,
172                   void *f_data);
173 static realtype DotProd(long int size, realtype *x1, realtype *x2);
174 static void BSend(MPI_Comm comm, long int my_pe, long int isubx,
175                  long int isuby, long int dsizex, long int dsizey,
176                  realtype *cdata);
177 static void BRecvPost(MPI_Comm comm, MPI_Request request[], long int my_pe,
178                      long int isubx, long int isuby,
179                      long int dsizex, long int dsizey,
180                      realtype *cext, realtype *buffer);
181 static void BRecvWait(MPI_Request request[], long int isubx,
182                      long int isuby, long int dsizex, realtype *cext,
183                      realtype *buffer);
184 static int check_flag(void *flagvalue, char *funcname, int opt, int id);
185
186 /*
187  *-----
188  * MAIN PROGRAM
189  *-----
190  */
191
192 int main(int argc, char *argv[])
193 {
194     MPI_Comm comm;
195     void *kmem, *pdata;
196     UserData data;
197     N_Vector cc, sc, constraints;
198     int globalstrategy;
199     long int Nlocal;
200     realtype fnormtol, scsteptol, dq_rel_uu;
201     int flag, maxl, maxlrst;
202     long int mu, ml;
203     int my_pe, npes, npelast = NPEX*NPEY-1;
204
205     data = NULL;
206     kmem = pdata = NULL;
207     cc = sc = constraints = NULL;
208
209     /* Get processor number and total number of pe's */
210     MPI_Init(&argc, &argv);
211     comm = MPI_COMM_WORLD;
212     MPI_Comm_size(comm, &npes);
213     MPI_Comm_rank(comm, &my_pe);
214

```

```

215 if (npes != NPEX*NPEY) {
216     if (my_pe == 0)
217         printf("\nMPI_ERROR(0): npes=%d is not equal to NPEX*NPEY=%d\n", npes, NPEX*NPEY);
218     return(1);
219 }
220
221 /* Allocate memory, and set problem data, initial values, tolerances */
222
223 /* Set local length */
224 Nlocal = NUM_SPECIES*MXSUB*MYSUB;
225
226 /* Allocate and initialize user data block */
227 data = AllocUserData();
228 if (check_flag((void *)data, "AllocUserData", 2, my_pe)) MPI_Abort(comm, 1);
229 InitUserData(my_pe, Nlocal, comm, data);
230
231 /* Choose global strategy */
232 globalstrategy = KIN_INEXACT_NEWTON;
233
234 /* Allocate and initialize vectors */
235 cc = N_VNew_Parallel(comm, Nlocal, NEQ);
236 if (check_flag((void *)cc, "N_VNew_Parallel", 0, my_pe)) MPI_Abort(comm, 1);
237 sc = N_VNew_Parallel(comm, Nlocal, NEQ);
238 if (check_flag((void *)sc, "N_VNew_Parallel", 0, my_pe)) MPI_Abort(comm, 1);
239 data->rates = N_VNew_Parallel(comm, Nlocal, NEQ);
240 if (check_flag((void *)data->rates, "N_VNew_Parallel", 0, my_pe)) MPI_Abort(comm, 1);
241 constraints = N_VNew_Parallel(comm, Nlocal, NEQ);
242 if (check_flag((void *)constraints, "N_VNew_Parallel", 0, my_pe)) MPI_Abort(comm, 1);
243 N_VConst(ZERO, constraints);
244
245 SetInitialProfiles(cc, sc);
246
247 fnormtol = FTOL; scsteptol = STOL;
248
249 /* Call KINCreate/KINMalloc to initialize KINSOL:
250     nvSpec points to machine environment data
251     A pointer to KINSOL problem memory is returned and stored in kmem. */
252 kmem = KINCreate();
253 if (check_flag((void *)kmem, "KINCreate", 0, my_pe)) MPI_Abort(comm, 1);
254
255 /* Vector cc passed as template vector. */
256 flag = KINMalloc(kmem, func, cc);
257 if (check_flag(&flag, "KINMalloc", 1, my_pe)) MPI_Abort(comm, 1);
258
259 flag = KINSetFdata(kmem, data);
260 if (check_flag(&flag, "KINSetFdata", 1, my_pe)) MPI_Abort(comm, 1);
261
262 flag = KINSetConstraints(kmem, constraints);
263 if (check_flag(&flag, "KINSetConstraints", 1, my_pe)) MPI_Abort(comm, 1);
264
265 /* We no longer need the constraints vector since KINSetConstraints
266     creates a private copy for KINSOL to use. */
267 N_VDestroy_Parallel(constraints);
268

```

```

269 flag = KINSetFuncNormTol(kmem, fnormtol);
270 if (check_flag(&flag, "KINSetFuncNormTol", 1, my_pe)) MPI_Abort(comm, 1);
271
272 flag = KINSetScaledStepTol(kmem, scsteptol);
273 if (check_flag(&flag, "KINSetScaledStepTol", 1, my_pe)) MPI_Abort(comm, 1);
274
275 /* Call KINBBDPrecAlloc to initialize and allocate memory for the
276    band-block-diagonal preconditioner, and specify the local and
277    communication functions func_local and gcomm=NULL (all communication
278    needed for the func_local is already done in func). */
279 dq_rel_uu = ZERO;
280 mu = ml = 2*NUM_SPECIES - 1;
281
282 pdata = KINBBDPrecAlloc(kmem, Nlocal, mu, ml, dq_rel_uu, func_local, NULL);
283 if (check_flag((void *)pdata, "KINBBDPrecAlloc", 0, my_pe))
284     MPI_Abort(comm, 1);
285
286 /* Call KINBBDSpgmr to specify the linear solver KINSPGMR
287    with preconditioner KINBBDPRE */
288 maxl = 20; maxlrst = 2;
289 flag = KINBBDSpgmr(kmem, maxl, pdata);
290 if (check_flag(&flag, "KINBBDSpgmr", 1, my_pe))
291     MPI_Abort(comm, 1);
292
293 flag = KINSPgmrSetMaxRestarts(kmem, maxlrst);
294 if (check_flag(&flag, "KINSPgmrSetMaxRestarts", 1, my_pe))
295     MPI_Abort(comm, 1);
296
297 /* Print out the problem size, solution parameters, initial guess. */
298 if (my_pe == 0)
299     PrintHeader(globalstrategy, maxl, maxlrst, mu, ml, fnormtol, scsteptol);
300
301 /* call KINSol and print output concentration profile */
302 flag = KINSol(kmem, /* KINSol memory block */
303              cc, /* initial guess on input; solution vector */
304              globalstrategy, /* global strategy choice */
305              sc, /* scaling vector, for the variable cc */
306              sc); /* scaling vector for function values fval */
307 if (check_flag(&flag, "KINSol", 1, my_pe)) MPI_Abort(comm, 1);
308
309 if (my_pe == 0) printf("\n\nComputed equilibrium species concentrations:\n");
310 if (my_pe == 0 || my_pe==npelast) PrintOutput(my_pe, comm, cc);
311
312 /* Print final statistics and free memory */
313 if (my_pe == 0)
314     PrintFinalStats(kmem);
315
316 N_VDestroy_Parallel(cc);
317 N_VDestroy_Parallel(sc);
318 KINBBDPrecFree(pdata);
319 KINFree(kmem);
320 FreeUserData(data);
321
322 MPI_Finalize();

```

```

323
324     return(0);
325 }
326
327 /* Readability definitions used in other routines below */
328
329 #define acoef  (data->acoef)
330 #define bcoef  (data->bcoef)
331 #define cox    (data->cox)
332 #define coy    (data->coy)
333
334 /*
335  *-----
336  * FUNCTIONS CALLED BY KINSOL
337  *-----
338  */
339
340 /*
341  * ccomm routine. This routine performs all communication
342  * between processors of data needed to calculate f.
343  */
344
345 static void ccomm(long int Nlocal, N_Vector cc, void *userdata)
346 {
347
348     realtype *cdata, *cext, buffer[2*NUM_SPECIES*MYSUB];
349     UserData data;
350     MPI_Comm comm;
351     long int my_pe, isubx, isuby, nsmxsub, nsmysub;
352     MPI_Request request[4];
353
354     /* Get comm, my_pe, subgrid indices, data sizes, extended array cext */
355     data = (UserData) userdata;
356     comm = data->comm; my_pe = data->my_pe;
357     isubx = data->isubx; isuby = data->isuby;
358     nsmxsub = data->nsmxsub;
359     nsmysub = NUM_SPECIES*MYSUB;
360     cext = data->cext;
361
362     cdata = NV_DATA_P(cc);
363
364     /* Start receiving boundary data from neighboring PEs */
365     BRecvPost(comm, request, my_pe, isubx, isuby, nsmxsub, nsmysub, cext, buffer);
366
367     /* Send data from boundary of local grid to neighboring PEs */
368     BSend(comm, my_pe, isubx, isuby, nsmxsub, nsmysub, cdata);
369
370     /* Finish receiving boundary data from neighboring PEs */
371     BRecvWait(request, isubx, isuby, nsmxsub, cext, buffer);
372
373 }
374
375 /*
376  * System function for predator-prey system - calculation part

```

```

377  */
378
379 static void func_local(long int Nlocal, N_Vector cc, N_Vector fval, void *f_data)
380 {
381     realtype xx, yy, *cxy, *rxy, *fxy, dcydi, dcyui, dcxli, dcxri;
382     realtype *cext, dely, delx, *cdata;
383     long int i, jx, jy, is, ly;
384     long int isubx, isuby, nsmxsub, nsmxsub2;
385     long int shifty, offsetc, offsetce, offsetcl, offsetcr, offsetcd, offsetcu;
386     UserData data;
387
388     data = (UserData)f_data;
389     cdata = NV_DATA_P(cc);
390
391     /* Get subgrid indices, data sizes, extended work array cext */
392     isubx = data->isubx; isuby = data->isuby;
393     nsmxsub = data->nsmxsub; nsmxsub2 = data->nsmxsub2;
394     cext = data->cext;
395
396     /* Copy local segment of cc vector into the working extended array cext */
397     offsetc = 0;
398     offsetce = nsmxsub2 + NUM_SPECIES;
399     for (ly = 0; ly < MYSUB; ly++) {
400         for (i = 0; i < nsmxsub; i++) cext[offsetce+i] = cdata[offsetc+i];
401         offsetc = offsetc + nsmxsub;
402         offsetce = offsetce + nsmxsub2;
403     }
404
405     /* To facilitate homogeneous Neumann boundary conditions, when this is a
406        boundary PE, copy data from the first interior mesh line of cc to cext */
407
408     /* If isuby = 0, copy x-line 2 of cc to cext */
409     if (isuby == 0) {
410         for (i = 0; i < nsmxsub; i++) cext[NUM_SPECIES+i] = cdata[nsmxsub+i];
411     }
412
413     /* If isuby = NPEY-1, copy x-line MYSUB-1 of cc to cext */
414     if (isuby == NPEY-1) {
415         offsetc = (MYSUB-2)*nsmxsub;
416         offsetce = (MYSUB+1)*nsmxsub2 + NUM_SPECIES;
417         for (i = 0; i < nsmxsub; i++) cext[offsetce+i] = cdata[offsetc+i];
418     }
419
420     /* If isubx = 0, copy y-line 2 of cc to cext */
421     if (isubx == 0) {
422         for (ly = 0; ly < MYSUB; ly++) {
423             offsetc = ly*nsmxsub + NUM_SPECIES;
424             offsetce = (ly+1)*nsmxsub2;
425             for (i = 0; i < NUM_SPECIES; i++) cext[offsetce+i] = cdata[offsetc+i];
426         }
427     }
428
429     /* If isubx = NPEX-1, copy y-line MXSUB-1 of cc to cext */
430     if (isubx == NPEX-1) {

```

```

431     for (ly = 0; ly < MYSUB; ly++) {
432         offsetc = (ly+1)*nsmxsub - 2*NUM_SPECIES;
433         offsetce = (ly+2)*nsmxsub2 - NUM_SPECIES;
434         for (i = 0; i < NUM_SPECIES; i++) cext[offsetce+i] = cdata[offsetc+i];
435     }
436 }
437
438 /* Loop over all mesh points, evaluating rate arra at each point */
439 delx = data->dx;
440 dely = data->dy;
441 shifty = (MXSUB+2)*NUM_SPECIES;
442
443 for (jy = 0; jy < MYSUB; jy++) {
444
445     yy = dely*(jy + isuby * MYSUB);
446
447     for (jx = 0; jx < MXSUB; jx++) {
448
449         xx = delx * (jx + isubx * MXSUB);
450         cxy = IJ_Vptr(cc,jx,jy);
451         rxy = IJ_Vptr(data->rates,jx,jy);
452         fxy = IJ_Vptr(fval,jx,jy);
453
454         WebRate(xx, yy, cxy, rxy, f_data);
455
456         offsetc = (jx+1)*NUM_SPECIES + (jy+1)*NSMXSUB2;
457         offsetcd = offsetc - shifty;
458         offsetcu = offsetc + shifty;
459         offsetcl = offsetc - NUM_SPECIES;
460         offsetcr = offsetc + NUM_SPECIES;
461
462         for (is = 0; is < NUM_SPECIES; is++) {
463
464             /* differencing in x */
465             dcydi = cext[offsetc+is] - cext[offsetcd+is];
466             dcyui = cext[offsetcu+is] - cext[offsetc+is];
467
468             /* differencing in y */
469             dcxli = cext[offsetc+is] - cext[offsetcl+is];
470             dcxri = cext[offsetcr+is] - cext[offsetc+is];
471
472             /* compute the value at xx , yy */
473             fxy[is] = (coy)[is] * (dcyui - dcydi) +
474                 (cox)[is] * (dcxri - dcxli) + rxy[is];
475
476         } /* end of is loop */
477
478     } /* end of jx loop */
479
480 } /* end of jy loop */
481 }
482
483 /*
484 * System function routine. Evaluate f(cc). First call ccomm to do

```

```

485  * communication of subgrid boundary data into cext.  Then calculate f
486  * by a call to func_local.
487  */
488
489  static void func(N_Vector cc, N_Vector fval, void *f_data)
490  {
491      UserData data;
492
493      data = (UserData) f_data;
494
495      /* Call ccomm to do inter-processor communicaiton */
496      ccomm(data->Nlocal, cc, data);
497
498      /* Call func_local to calculate all right-hand sides */
499      func_local(data->Nlocal, cc, fval, data);
500  }
501
502  /*
503   * Interaction rate function routine
504   */
505
506  static void WebRate(realtype xx, realtype yy, realtype *cxy, realtype *ratesxy,
507                    void *f_data)
508  {
509      long int i;
510      realtype fac;
511      UserData data;
512
513      data = (UserData)f_data;
514
515      for (i = 0; i<NUM_SPECIES; i++)
516          ratesxy[i] = DotProd(NUM_SPECIES, cxy, acoef[i]);
517
518      fac = ONE + ALPHA * xx * yy;
519
520      for (i = 0; i < NUM_SPECIES; i++)
521          ratesxy[i] = cxy[i] * ( bcoef[i] * fac + ratesxy[i] );
522  }
523
524  /*
525   * Dot product routine for realtype arrays
526   */
527
528  static realtype DotProd(long int size, realtype *x1, realtype *x2)
529  {
530      long int i;
531      realtype *xx1, *xx2, temp = ZERO;
532
533      xx1 = x1; xx2 = x2;
534      for (i = 0; i < size; i++) temp += (*xx1++) * (*xx2++);
535
536      return(temp);
537  }
538

```

```

539  /*
540  *-----
541  * PRIVATE FUNCTIONS
542  *-----
543  */
544
545  /*
546  * Allocate memory for data structure of type UserData
547  */
548
549  static UserData AllocUserData(void)
550  {
551      UserData data;
552
553      data = (UserData) malloc(sizeof *data);
554
555      acoef = denalloc(NUM_SPECIES);
556      bcoef = (realtype *)malloc(NUM_SPECIES * sizeof(realtype));
557      cox   = (realtype *)malloc(NUM_SPECIES * sizeof(realtype));
558      coy   = (realtype *)malloc(NUM_SPECIES * sizeof(realtype));
559
560      return(data);
561  }
562
563  /*
564  * Load problem constants in data
565  */
566
567  static void InitUserData(long int my_pe, long int Nlocal, MPI_Comm comm, UserData data)
568  {
569      long int i, j, np;
570      realtype *a1,*a2, *a3, *a4, dx2, dy2;
571
572      data->mx = MX;
573      data->my = MY;
574      data->ns = NUM_SPECIES;
575      data->np = NUM_SPECIES/2;
576      data->ax = AX;
577      data->ay = AY;
578      data->dx = (data->ax)/(MX-1);
579      data->dy = (data->ay)/(MY-1);
580      data->my_pe = my_pe;
581      data->Nlocal = Nlocal;
582      data->comm = comm;
583      data->isuby = my_pe/NPEX;
584      data->isubx = my_pe - data->isuby*NPEX;
585      data->nsmxsub = NUM_SPECIES * MXSUB;
586      data->nsmxsub2 = NUM_SPECIES * (MXSUB+2);
587
588      /* Set up the coefficients a and b plus others found in the equations */
589      np = data->np;
590
591      dx2=(data->dx)*(data->dx); dy2=(data->dy)*(data->dy);
592

```

```

593     for (i = 0; i < np; i++) {
594         a1= &(acoef[i][np]);
595         a2= &(acoef[i+np][0]);
596         a3= &(acoef[i][0]);
597         a4= &(acoef[i+np][np]);
598
599         /* Fill in the portion of acoef in the four quadrants, row by row */
600         for (j = 0; j < np; j++) {
601             *a1++ = -GG;
602             *a2++ = EE;
603             *a3++ = ZERO;
604             *a4++ = ZERO;
605         }
606
607         /* and then change the diagonal elements of acoef to -AA */
608         acoef[i][i]=-AA;
609         acoef[i+np][i+np] = -AA;
610
611         bcoef[i] = BB;
612         bcoef[i+np] = -BB;
613
614         cox[i]=DPREY/dx2;
615         cox[i+np]=DPRED/dx2;
616
617         coy[i]=DPREY/dy2;
618         coy[i+np]=DPRED/dy2;
619     }
620 }
621
622 /*
623  * Free data memory
624  */
625
626 static void FreeUserData(UserData data)
627 {
628
629     denfree(acoef);
630     free(bcoef);
631     free(cox); free(coy);
632     N_VDestroy_Parallel(data->rates);
633
634     free(data);
635
636 }
637
638 /*
639  * Set initial conditions in cc
640  */
641
642 static void SetInitialProfiles(N_Vector cc, N_Vector sc)
643 {
644     int i, jx, jy;
645     realtype *cloc, *sloc;
646     realtype ctemp[NUM_SPECIES], stemp[NUM_SPECIES];

```

```

647
648 /* Initialize arrays ctemp and stemp used in the loading process */
649 for (i = 0; i < NUM_SPECIES/2; i++) {
650     ctemp[i] = PREYIN;
651     stemp[i] = ONE;
652 }
653 for (i = NUM_SPECIES/2; i < NUM_SPECIES; i++) {
654     ctemp[i] = PREDIN;
655     stemp[i] = RCONST(0.00001);
656 }
657
658 /* Load initial profiles into cc and sc vector from ctemp and stemp. */
659 for (jy = 0; jy < MYSUB; jy++) {
660     for (jx=0; jx < MXSUB; jx++) {
661         cloc = IJ_Vptr(cc,jx,jy);
662         sloc = IJ_Vptr(sc,jx,jy);
663         for (i = 0; i < NUM_SPECIES; i++){
664             cloc[i] = ctemp[i];
665             sloc[i] = stemp[i];
666         }
667     }
668 }
669
670 }
671
672 /*
673  * Print first lines of output (problem description)
674  */
675
676 static void PrintHeader(int globalstrategy, int maxl, int maxlrst,
677                        long int mu, long int ml,
678                        realtype fnormtol, realtype scsteptol)
679 {
680     printf("\nPredator-prey test problem-- KINSol (parallel-BBD version)\n\n");
681
682     printf("Mesh dimensions = %d X %d\n", MX, MY);
683     printf("Number of species = %d\n", NUM_SPECIES);
684     printf("Total system size = %d\n", NEQ);
685     printf("Subgrid dimensions = %d X %d\n", MXSUB, MYSUB);
686     printf("Processor array is %d X %d\n\n", NPEX, NPEY);
687     printf("Flag globalstrategy = %d (1 = Inex. Newton, 2 = Linesearch)\n",
688           globalstrategy);
689     printf("Linear solver is SPGMR with maxl = %d, maxlrst = %d\n",
690           maxl, maxlrst);
691     printf("Preconditioning uses band-block-diagonal matrix from KINBBDPRE\n");
692     printf("  with matrix half-bandwidths ml, mu = %ld %ld\n", ml, mu);
693     #if defined(SUNDIALS_EXTENDED_PRECISION)
694         printf("Tolerance parameters:  fnormtol = %Lg    scsteptol = %Lg\n",
695               fnormtol, scsteptol);
696     #elif defined(SUNDIALS_DOUBLE_PRECISION)
697         printf("Tolerance parameters:  fnormtol = %lg    scsteptol = %lg\n",
698               fnormtol, scsteptol);
699     #else
700         printf("Tolerance parameters:  fnormtol = %g    scsteptol = %g\n",

```

```

701         fnormtol, scsteptol);
702 #endif
703
704     printf("\nInitial profile of concentration\n");
705 #if defined(SUNDIALS_EXTENDED_PRECISION)
706     printf("At all mesh points:  %Lg %Lg %Lg   %Lg %Lg %Lg\n", PREYIN,PREYIN,PREYIN,
707           PREDIN,PREDIN,PREDIN);
708 #elif defined(SUNDIALS_DOUBLE_PRECISION)
709     printf("At all mesh points:  %lg %lg %lg   %lg %lg %lg\n", PREYIN,PREYIN,PREYIN,
710           PREDIN,PREDIN,PREDIN);
711 #else
712     printf("At all mesh points:  %g %g %g   %g %g %g\n", PREYIN,PREYIN,PREYIN,
713           PREDIN,PREDIN,PREDIN);
714 #endif
715 }
716
717 /*
718  * Print sample of current cc values
719  */
720
721 static void PrintOutput(long int my_pe, MPI_Comm comm, N_Vector cc)
722 {
723     int is, i0, npelast;
724     realtype *ct, tempc[NUM_SPECIES];
725     MPI_Status status;
726
727     npelast = NPEX*NPEY - 1;
728
729     ct = NV_DATA_P(cc);
730
731     /* Send the cc values (for all species) at the top right mesh point to PE 0 */
732     if (my_pe == npelast) {
733         i0 = NUM_SPECIES*(MXSUB*MYSUB-1);
734         if (npelast!=0)
735             MPI_Send(&ct[i0],NUM_SPECIES,PVEC_REAL_MPI_TYPE,0,0,comm);
736         else /* single processor case */
737             for (is = 0; is < NUM_SPECIES; is++) tempc[is]=ct[i0+is];
738     }
739
740     /* On PE 0, receive the cc values at top right, then print performance data
741        and sampled solution values */
742     if (my_pe == 0) {
743
744         if (npelast != 0)
745             MPI_Recv(&tempc[0],NUM_SPECIES,PVEC_REAL_MPI_TYPE,npelast,0,comm,&status);
746
747         printf("\nAt bottom left:");
748         for (is = 0; is < NUM_SPECIES; is++){
749             if ((is%6)*6== is) printf("\n");
750 #if defined(SUNDIALS_EXTENDED_PRECISION)
751             printf(" %Lg",ct[is]);
752 #elif defined(SUNDIALS_DOUBLE_PRECISION)
753             printf(" %lg",ct[is]);
754 #else
755             printf(" %g",ct[is]);
756 #endif

```

```

755         printf(" %g",ct[is]);
756 #endif
757     }
758
759     printf("\n\nAt top right:");
760     for (is = 0; is < NUM_SPECIES; is++) {
761         if ((is%6)*6 == is) printf("\n");
762 #if defined(SUNDIALS_EXTENDED_PRECISION)
763         printf(" %Lg",tempc[is]);
764 #elif defined(SUNDIALS_DOUBLE_PRECISION)
765         printf(" %lg",tempc[is]);
766 #else
767         printf(" %g",tempc[is]);
768 #endif
769     }
770     printf("\n\n");
771 }
772 }
773
774 /*
775  * Print final statistics contained in iopt
776  */
777
778 static void PrintFinalStats(void *kmem)
779 {
780     long int nni, nfe, nli, npe, nps, ncfl, nfeSG;
781     int flag;
782
783     flag = KINGetNumNonlinSolvIters(kmem, &nni);
784     check_flag(&flag, "KINGetNumNonlinSolvIters", 1, 0);
785     flag = KINGetNumFuncEvals(kmem, &nfe);
786     check_flag(&flag, "KINGetNumFuncEvals", 1, 0);
787     flag = KINSpgmrGetNumLinIters(kmem, &nli);
788     check_flag(&flag, "KINSpgmrGetNumLinIters", 1, 0);
789     flag = KINSpgmrGetNumPrecEvals(kmem, &npe);
790     check_flag(&flag, "KINSpgmrGetNumPrecEvals", 1, 0);
791     flag = KINSpgmrGetNumPrecSolves(kmem, &nps);
792     check_flag(&flag, "KINSpgmrGetNumPrecSolves", 1, 0);
793     flag = KINSpgmrGetNumConvFails(kmem, &ncfl);
794     check_flag(&flag, "KINSpgmrGetNumConvFails", 1, 0);
795     flag = KINSpgmrGetNumFuncEvals(kmem, &nfeSG);
796     check_flag(&flag, "KINSpgmrGetNumFuncEvals", 1, 0);
797
798     printf("\nFinal Statistics.. \n\n");
799     printf("nni      = %5ld      nli      = %5ld\n", nni, nli);
800     printf("nfe      = %5ld      nfeSG = %5ld\n", nfe, nfeSG);
801     printf("nps      = %5ld      npe      = %5ld      ncfl = %5ld\n", nps, npe, ncfl);
802
803 }
804
805 /*
806  * Routine to send boundary data to neighboring PEs
807  */
808

```

```

809 static void BSend(MPI_Comm comm, long int my_pe,
810                   long int isubx, long int isuby,
811                   long int dsizex, long int dsizey, realtype *cdata)
812 {
813     int i, ly;
814     long int offsetc, offsetbuf;
815     realtype bufleft[NUM_SPECIES*MYSUB], bufright[NUM_SPECIES*MYSUB];
816
817     /* If isuby > 0, send data from bottom x-line of u */
818     if (isuby != 0)
819         MPI_Send(&cdata[0], dsizex, PVEC_REAL_MPI_TYPE, my_pe-NPEX, 0, comm);
820
821     /* If isuby < NPEY-1, send data from top x-line of u */
822     if (isuby != NPEY-1) {
823         offsetc = (MYSUB-1)*dsizex;
824         MPI_Send(&cdata[offsetc], dsizex, PVEC_REAL_MPI_TYPE, my_pe+NPEX, 0, comm);
825     }
826
827     /* If isubx > 0, send data from left y-line of u (via bufleft) */
828     if (isubx != 0) {
829         for (ly = 0; ly < MYSUB; ly++) {
830             offsetbuf = ly*NUM_SPECIES;
831             offsetc = ly*dsizex;
832             for (i = 0; i < NUM_SPECIES; i++)
833                 bufleft[offsetbuf+i] = cdata[offsetc+i];
834         }
835         MPI_Send(&bufleft[0], dsizey, PVEC_REAL_MPI_TYPE, my_pe-1, 0, comm);
836     }
837
838     /* If isubx < NPEX-1, send data from right y-line of u (via bufright) */
839     if (isubx != NPEX-1) {
840         for (ly = 0; ly < MYSUB; ly++) {
841             offsetbuf = ly*NUM_SPECIES;
842             offsetc = offsetbuf*MXSUB + (MXSUB-1)*NUM_SPECIES;
843             for (i = 0; i < NUM_SPECIES; i++)
844                 bufright[offsetbuf+i] = cdata[offsetc+i];
845         }
846         MPI_Send(&bufright[0], dsizey, PVEC_REAL_MPI_TYPE, my_pe+1, 0, comm);
847     }
848 }
849
850 /*
851  * Routine to start receiving boundary data from neighboring PEs.
852  * Notes:
853  * 1) buffer should be able to hold 2*NUM_SPECIES*MYSUB realtype entries,
854  *    should be passed to both the BRecvPost and BRecvWait functions, and
855  *    should not be manipulated between the two calls.
856  * 2) request should have 4 entries, and should be passed in both calls also.
857  */
858
859 static void BRecvPost(MPI_Comm comm, MPI_Request request[], long int my_pe,
860                      long int isubx, long int isuby,
861                      long int dsizex, long int dsizey,
862                      realtype *cext, realtype *buffer)

```

```

863 {
864     long int offsetce;
865
866     /* Have bufleft and bufright use the same buffer */
867     realtype *bufleft = buffer, *bufright = buffer+NUM_SPECIES*MYSUB;
868
869     /* If isuby > 0, receive data for bottom x-line of cext */
870     if (isuby != 0)
871         MPI_Irecv(&cext[NUM_SPECIES], dsizex, PVEC_REAL_MPI_TYPE,
872                 my_pe-NPEX, 0, comm, &request[0]);
873
874     /* If isuby < NPEY-1, receive data for top x-line of cext */
875     if (isuby != NPEY-1) {
876         offsetce = NUM_SPECIES*(1 + (MYSUB+1)*(MXSUB+2));
877         MPI_Irecv(&cext[offsetce], dsizex, PVEC_REAL_MPI_TYPE,
878                 my_pe+NPEX, 0, comm, &request[1]);
879     }
880
881     /* If isubx > 0, receive data for left y-line of cext (via bufleft) */
882     if (isubx != 0) {
883         MPI_Irecv(&bufleft[0], dsizey, PVEC_REAL_MPI_TYPE,
884                 my_pe-1, 0, comm, &request[2]);
885     }
886
887     /* If isubx < NPEX-1, receive data for right y-line of cext (via bufright) */
888     if (isubx != NPEX-1) {
889         MPI_Irecv(&bufright[0], dsizey, PVEC_REAL_MPI_TYPE,
890                 my_pe+1, 0, comm, &request[3]);
891     }
892 }
893
894 /*
895  * Routine to finish receiving boundary data from neighboring PEs.
896  * Notes:
897  * 1) buffer should be able to hold 2*NUM_SPECIES*MYSUB realtype entries,
898  *    should be passed to both the BRecvPost and BRecvWait functions, and
899  *    should not be manipulated between the two calls.
900  * 2) request should have 4 entries, and should be passed in both calls also.
901  */
902
903 static void BRecvWait(MPI_Request request[], long int isubx,
904                      long int isuby, long int dsizex, realtype *cext,
905                      realtype *buffer)
906 {
907     int i, ly;
908     long int dsizex2, offsetce, offsetbuf;
909     realtype *bufleft = buffer, *bufright = buffer+NUM_SPECIES*MYSUB;
910     MPI_Status status;
911
912     dsizex2 = dsizex + 2*NUM_SPECIES;
913
914     /* If isuby > 0, receive data for bottom x-line of cext */
915     if (isuby != 0)
916         MPI_Wait(&request[0], &status);

```

```

917
918 /* If isuby < NPEY-1, receive data for top x-line of cext */
919 if (isuby != NPEY-1)
920     MPI_Wait(&request[1],&status);
921
922 /* If isubx > 0, receive data for left y-line of cext (via bufleft) */
923 if (isubx != 0) {
924     MPI_Wait(&request[2],&status);
925
926     /* Copy the buffer to cext */
927     for (ly = 0; ly < MYSUB; ly++) {
928         offsetbuf = ly*NUM_SPECIES;
929         offsetce = (ly+1)*dsizex2;
930         for (i = 0; i < NUM_SPECIES; i++)
931             cext[offsetce+i] = bufleft[offsetbuf+i];
932     }
933 }
934
935 /* If isubx < NPEX-1, receive data for right y-line of cext (via bufright) */
936 if (isubx != NPEX-1) {
937     MPI_Wait(&request[3],&status);
938
939     /* Copy the buffer to cext */
940     for (ly = 0; ly < MYSUB; ly++) {
941         offsetbuf = ly*NUM_SPECIES;
942         offsetce = (ly+2)*dsizex2 - NUM_SPECIES;
943         for (i = 0; i < NUM_SPECIES; i++)
944             cext[offsetce+i] = bufright[offsetbuf+i];
945     }
946 }
947 }
948 /*
949  * Check function return value...
950  *   opt == 0 means SUNDIALS function allocates memory so check if
951  *       returned NULL pointer
952  *   opt == 1 means SUNDIALS function returns a flag so check if
953  *       flag >= 0
954  *   opt == 2 means function allocates memory so check if returned
955  *       NULL pointer
956  */
957
958 static int check_flag(void *flagvalue, char *funcname, int opt, int id)
959 {
960     int *errflag;
961
962     /* Check if SUNDIALS function returned NULL pointer - no memory allocated */
963     if (opt == 0 && flagvalue == NULL) {
964         fprintf(stderr,
965             "\nSUNDIALS_ERROR(%d): %s() failed - returned NULL pointer\n\n",
966             id, funcname);
967         return(1);
968     }
969
970     /* Check if flag < 0 */

```

```

971     else if (opt == 1) {
972         errflag = (int *) flagvalue;
973         if (*errflag < 0) {
974             fprintf(stderr,
975                 "\nSUNDIALS_ERROR(%d): %s() failed with flag = %d\n\n",
976                 id, funcname, *errflag);
977             return(1);
978         }
979     }
980
981     /* Check if function returned NULL pointer - no memory allocated */
982     else if (opt == 2 && flagvalue == NULL) {
983         fprintf(stderr,
984             "\nMEMORY_ERROR(%d): %s() failed - returned NULL pointer\n\n",
985             id, funcname);
986         return(1);
987     }
988
989     return(0);
990 }

```

C Listing of kindiagsf.f

```

1      program kindiagsf
2      c -----
3      c $Revision: 1.13.2.1 $
4      c $Date: 2005/04/07 00:20:28 $
5      c -----
6      c Programmer(s): Allan Taylor, Alan Hindmarsh and
7      c                      Radu Serban @ LLNL
8      c -----
9      c Simple diagonal test with Fortran interface, using user-supplied
10     c preconditioner setup and solve routines (supplied in Fortran).
11     c
12     c This example does a basic test of the solver by solving the
13     c system:
14     c          f(u) = 0 for
15     c          f(u) = u(i)^2 - i^2
16     c
17     c No scaling is done.
18     c An approximate diagonal preconditioner is used.
19     c
20     c Execution command: kindiagsf
21     c -----
22     c
23     implicit none
24
25     integer ier, globalstrat, inopt, maxl, maxlrst
26     integer*4 PROBSIZE
27     parameter(PROBSIZE=128)
28     integer*4 neq, i, msbpre
29     integer*4 iopt(40)
30     double precision pp, fnormtol, scsteptol
31     double precision ropt(40), uu(PROBSIZE), scale(PROBSIZE)
32     double precision constr(PROBSIZE)
33
34     common /pcom/ pp(PROBSIZE)
35     common /psize/ neq
36
37     neq = PROBSIZE
38     globalstrat = 1
39     fnormtol = 1.0d-5
40     scsteptol = 1.0d-4
41     inopt = 0
42     maxl = 10
43     maxlrst = 2
44     msbpre = 5
45
46     c * * * * *
47
48     call fnvinit(neq, ier)
49     if (ier .ne. 0) then
50         write(6,1220) ier
51 1220    format('SUNDIALS_ERROR: FNVINITS returned IER = ', i2)
52     stop

```

```

53      endif
54
55      do 20 i = 1, neq
56          uu(i) = 2.0d0 * i
57          scale(i) = 1.0d0
58          constr(i) = 0.0d0
59 20  continue
60
61      call fkinmalloc(msbpre, fnormtol, scsteptol,
62      &                constr, inopt, iopt, ropt, ier)
63      if (ier .ne. 0) then
64          write(6,1230) ier
65 1230  format('SUNDIALS_ERROR: FKINMALLOC returned IER = ', i2)
66          call fnvfrees
67          stop
68      endif
69
70      call fkinspgmr(maxl, maxlrst, ier)
71      if (ier .ne. 0) then
72          write(6,1235) ier
73 1235  format('SUNDIALS_ERROR: FKINSPGMR returned IER = ', i2)
74          call fkinfree
75          call fnvfrees
76          stop
77      endif
78
79      call fkinspgmrsetprec(1, ier)
80
81      write(6,1240)
82 1240 format('Example program kindiagsf:''' This fkinsol example code',
83      1      ' solves a 128 eqn diagonal algebraic system.'/
84      2      ' Its purpose is to demonstrate the use of the Fortran',
85      3      ' interface''' in a serial environment.''''
86      4      ' globalstrategy = KIN_INEXACT-NEWTON')
87
88      call fkinsol(uu, globalstrat, scale, scale, ier)
89      if (ier .lt. 0) then
90          write(6,1242) ier, iopt(15)
91 1242  format('SUNDIALS_ERROR: FKINSOL returned IER = ', i2, /,
92      1      ' Linear Solver returned IER = ', i2)
93          call fkinfree
94          call fnvfrees
95          stop
96      endif
97
98      write(6,1245) ier
99 1245 format('/' FKINSOL return code is ', i3)
100
101      write(6,1246)
102 1246 format('/' The resultant values of uu are: '/')
103
104      do 30 i = 1, neq, 4
105          write(6,1256) i, uu(i), uu(i+1), uu(i+2), uu(i+3)
106 1256  format(i4, 4(1x, f10.6))

```

```

107 30 continue
108
109 write(6,1267) iopt(4), iopt(11), iopt(5), iopt(12), iopt(13),
110 1 iopt(14)
111 1267 format(// 'Final statistics: '//
112 1 ' nni = ', i4, ', nli = ', i4, ', nfe = ', i4,
113 2 ', npe = ', i4, ', nps = ', i4, ', ncfl = ', i4)
114
115 call fkinfree
116 call fnvfrees
117
118 stop
119 end
120
121 c * * * * *
122 c The function defining the system  $f(u) = 0$  must be defined by a Fortran
123 c function of the following form.
124
125 subroutine fkfun(uu, fval)
126
127 implicit none
128
129 integer*4 neq, i
130 double precision fval(*), uu(*)
131
132 common /psize/ neq
133
134 do 10 i = 1, neq
135 fval(i) = uu(i) * uu(i) - i * i
136 10 continue
137 return
138 end
139
140
141 c * * * * *
142 c The routine kpreco is the preconditioner setup routine. It must have
143 c that specific name be used in order that the c code can find and link
144 c to it. The argument list must also be as illustrated below:
145
146 subroutine fkpset(udata, uscale, fdata, fscale,
147 1 vtemp1, vtemp2, ier)
148
149 implicit none
150
151 integer ier
152 integer*4 neq, i
153 double precision pp
154 double precision udata(*), uscale(*), fdata(*), fscale(*)
155 double precision vtemp1(*), vtemp2(*)
156
157 common /pcom/ pp(128)
158 common /psize/ neq
159
160 do 10 i = 1, neq

```

```

161         pp(i) = 0.5d0 / (udata(i) + 5.0d0)
162 10    continue
163     ier = 0
164
165     return
166     end
167
168
169 c * * * * *
170 c     The routine kpsol is the preconditioner solve routine. It must have
171 c     that specific name be used in order that the c code can find and link
172 c     to it. The argument list must also be as illustrated below:
173
174     subroutine fkpsol(udata, uscale, fdata, fscale,
175 1          vv, ftem, ier)
176
177     implicit none
178
179     integer ier
180     integer*4 neq, i
181     double precision pp
182     double precision udata(*), uscale(*), fdata(*), fscale(*)
183     double precision vv(*), ftem(*)
184
185     common /pcom/ pp(128)
186     common /psize/ neq
187
188     do 10 i = 1, neq
189         vv(i) = vv(i) * pp(i)
190 10    continue
191     ier = 0
192
193     return
194     end

```

D Listing of kindiagpf.f

```
1      program kindiagpf
2      c -----
3      c $Revision: 1.13.2.1 $
4      c $Date: 2005/04/07 00:20:22 $
5      c -----
6      c Programmer(s): Allan G. Taylor, Alan C. Hindmarsh and
7      c                      Radu Serban @ LLNL
8      c -----
9      c Simple diagonal test with Fortran interface, using
10     c user-supplied preconditioner setup and solve routines (supplied
11     c in Fortran, below).
12     c
13     c This example does a basic test of the solver by solving the
14     c system:
15     c          f(u) = 0   for
16     c          f(u) = u(i)^2 - i^2
17     c
18     c No scaling is done.
19     c An approximate diagonal preconditioner is used.
20     c
21     c Execution command: mpirun -np 4 kindiagpf
22     c -----
23     c
24     c include "mpif.h"
25
26     integer ier, size, globalstrat, rank, inopt, mype, npes
27     integer maxl, maxlrst
28     integer*4 localsize
29     parameter(localsize=32)
30     integer*4 neq, nlocal, msbpre, baseadd, i, ii
31     integer*4 iopt(40)
32     double precision pp, fnormtol, scsteptol
33     double precision uu(localsize), scale(localsize)
34     double precision constr(localsize)
35
36     common /pcom/ pp(localsize), mype, npes, baseadd, nlocal
37
38     nlocal = localsize
39     neq = 4 * nlocal
40     globalstrat = 1
41     fnormtol = 1.0d-5
42     scsteptol = 1.0d-4
43     inopt = 0
44     maxl = 10
45     maxlrst = 2
46     msbpre = 5
47
48     c The user MUST call mpi_init, Fortran binding, for the fkinsol package
49     c to work. The communicator, MPI_COMM_WORLD, is the only one common
50     c between the Fortran and C bindings. So in the following, the communicator
51     c MPI_COMM_WORLD is used in calls to mpi_comm_size and mpi_comm_rank
52     c to determine the total number of processors and the rank (0 ... size-1)
```

```

53  c      number of this process.
54
55      call mpi_init(ier)
56      if (ier .ne. 0) then
57          write(6,1210) ier
58  1210      format('MPI_ERROR: MPI_INIT returned IER = ', i2)
59          stop
60      endif
61
62      call fnvinitp(nlocal, neq, ier)
63      if (ier .ne. 0) then
64          write(6,1220) ier
65  1220      format('SUNDIALS_ERROR: FNVINITP returned IER = ', i2)
66          call mpi_finalize(ier)
67          stop
68      endif
69
70      call mpi_comm_size(MPI_COMM_WORLD, size, ier)
71      if (ier .ne. 0) then
72          write(6,1222) ier
73  1222      format('MPI_ERROR: MPI_COMM_SIZE returned IER = ', i2)
74          call mpi_abort(MPI_COMM_WORLD, 1, ier)
75          stop
76      endif
77
78      if (size .ne. 4) then
79          write(6,1230)
80  1230      format('MPI_ERROR: must use 4 processes')
81          call mpi_finalize(ier)
82          stop
83      endif
84      npes = size
85
86      call mpi_comm_rank(MPI_COMM_WORLD, rank, ier)
87      if (ier .ne. 0) then
88          write(6,1224) ier
89  1224      format('MPI_ERROR: MPI_COMM_RANK returned IER = ', i2)
90          call mpi_abort(MPI_COMM_WORLD, 1, ier)
91          stop
92      endif
93
94      mype = rank
95      baseadd = mype * nlocal
96
97      do 20 ii = 1, nlocal
98          i = ii + baseadd
99          uu(ii) = 2.0d0 * i
100          scale(ii) = 1.0d0
101          constr(ii) = 0.0d0
102  20  continue
103
104      call fkinmalloc(msbpre, fnormtol, scsteptol,
105      &                  constr, inopt, iopt, ropt, ier)
106

```

```

107         if (ier .ne. 0) then
108             write(6,1231)ier
109 1231     format('SUNDIALS_ERROR: FKINMALLOC returned IER = ', i2)
110             call mpi_abort(MPI_COMM_WORLD, 1, ier)
111             stop
112         endif
113
114         call fkinspgmr(maxl, maxlrst, ier)
115         call fkinspgmrsetprec(1, ier)
116
117         if (mype .eq. 0) write(6,1240)
118 1240 format('Example program kindiagpf:''' This fkinsol example code',
119           1      ' solves a 128 eqn diagonal algebraic system.'/
120           2      ' Its purpose is to demonstrate the use of the Fortran',
121           3      ' interface''' in a parallel environment.'///
122           4      ' globalstrategy = KIN_INEXACT_NEWTON')
123
124         call fkinsol(uu, globalstrat, scale, scale, ier)
125         if (ier .lt. 0) then
126             write(6,1242) ier, iopt(15)
127 1242     format('SUNDIALS_ERROR: FKINSOL returned IER = ', i2, /,
128           1      '                      Linear Solver returned IER = ', i2)
129             call mpi_abort(MPI_COMM_WORLD, 1, ier)
130             stop
131         endif
132
133         if (mype .eq. 0) write(6,1245) ier
134 1245 format('/' FKINSOL return code is ', i4/)
135
136         if (mype .eq. 0) write(6,1246)
137 1246 format('/' The resultant values of uu (process 0) are: '/')
138
139         do 30 i = 1, nlocal, 4
140             if(mype .eq. 0) write(6,1256) i + baseadd, uu(i), uu(i+1),
141           1      uu(i+2), uu(i+3)
142 1256     format(i4, 4(1x, f10.6))
143 30     continue
144
145         if (mype .eq. 0) write(6,1267) iopt(4), iopt(11), iopt(5),
146           1      iopt(12), iopt(13), iopt(14)
147 1267 format(//'Final statistics: '//
148           1      ' nni = ', i4, ', nli = ', i4, ', nfe = ', i4,
149           2      ', npe = ', i4, ', nps=', i4, ', ncfl=', i4)
150
151         call fkinfree
152         call fnvfreep
153
154 c      An explicit call to mpi_finalize (Fortran binding) is required by
155 c      the constructs used in fkinsol.
156         call mpi_finalize(ier)
157
158         stop
159         end
160

```

```

161
162 c * * * * *
163 c      The function defining the system  $f(u) = 0$  must be defined by a Fortran
164 c      function with the following name and form.
165
166      subroutine fkfun(uu, fval)
167
168      implicit none
169
170      integer mype, npes
171      integer*4 baseadd, nlocal, i, localsize
172      parameter(localsize=32)
173      double precision pp
174      double precision fval(*), uu(*)
175
176      common /pcom/ pp(localsize), mype, npes, baseadd, nlocal
177
178      do 10 i = 1, nlocal
179 10      fval(i) = uu(i) * uu(i) - (i + baseadd) * (i + baseadd)
180
181      return
182      end
183
184
185 c * * * * *
186 c      The routine kpreco is the preconditioner setup routine. It must have
187 c      that specific name be used in order that the c code can find and link
188 c      to it. The argument list must also be as illustrated below:
189
190      subroutine fkpset(udata, uscale, fdata, fscale,
191 1      vtemp1, vtemp2, ier)
192
193      implicit none
194
195      integer ier, mype, npes
196      integer*4 localsize
197      parameter(localsize=32)
198      integer*4 baseadd, nlocal, i
199      double precision pp
200      double precision udata(*), uscale(*), fdata(*), fscale(*)
201      double precision vtemp1(*), vtemp2(*)
202
203      common /pcom/ pp(localsize), mype, npes, baseadd, nlocal
204
205      do 10 i = 1, nlocal
206 10      pp(i) = 0.5d0 / (udata(i)+ 5.0d0)
207
208      ier = 0
209
210      return
211      end
212
213
214 c * * * * *

```

```

215 c      The routine kpsol is the preconditioner solve routine. It must have
216 c      that specific name be used in order that the c code can find and link
217 c      to it. The argument list must also be as illustrated below:
218
219      subroutine fkpsol(udata, uscale, fdata, fscale,
220 1          vv, ftem, ier)
221
222      implicit none
223
224      integer ier, mype, npes
225      integer*4 baseadd, nlocal, i
226      integer*4 localsize
227      parameter(localsize=32)
228      double precision udata(*), uscale(*), fdata(*), fscale(*)
229      double precision vv(*), ftem(*)
230      double precision pp
231
232      common /pcom/ pp(localsize), mype, npes, baseadd, nlocal
233
234      do 10 i = 1, nlocal
235 10      vv(i) = vv(i) * pp(i)
236
237      ier = 0
238
239      return
240      end

```

